



2019  
**CFMOTO ZFORCE 1000 EPS LX**

STARTING AT  
**\$17,799\***



**Best 5 Year  
(LIMITED)  
Warranty \*\***

**CFMOTO.CA**



**WIND  
ZONE**  
windzone.ca

## 2019 CFMOTO ZFORCE 1000 EPS LX



**Best 5 Year  
(LIMITED)  
Warranty\*\***

ATHENS BLUE  
RED

### ENGINE

TYPE	V-Twin Cylinder, 4 strokes, 8 valves
DISPLACEMENT	962.6 cc
BORE & STROKE	91 x 74 mm (3.6 x 2.9 in)
COMPRESSION	10.6 : 1
ENGINE MANAGEMENT	BOSCH EFI and ignition system
MAXIMUM TORQUE	60.5 FT/LB @ 6200 rpm
MAXIMUM POWER OUTPUT	79 HP / 7000 rpm
COOLING SYSTEM	Liquid
STARTING	Electric
BATTERY	Yuasa, 30 Amp

### SIZE / WEIGHT

LENGTH x WIDTH x HEIGHT	2870 x 1510 x 1845 mm (113 x 59.4 x 72.6 in)
WHEELBASE	2040 mm (80.3 in)
SEAT HEIGHT	395 mm (15.6 in)
GROUND CLEARANCE	310 mm (12.2 in)
FUEL TANK CAPACITY	27 L (7.1 gal)
CURB WEIGHT	610 kg (1345 lbs)
TOWING CAPACITY	To come
REAR BOX CAPACITY	100 kg (220 lbs)



**GET IT ALL  
THE BEST!**  
PRICE, WARRANTY,  
FEATURES  
& ADVENTURE!

### STANDARD FEATURES AND BENEFITS

#### SAFETY

Passenger hold bar | Lateral mirrors | Horn  
ROPS certified Roll Cage | 4 points Seat belts | Hand brake  
Halogen hi & low beam | Hazard lights | Flashers

#### LOOK

High quality graphics | Premium glossy paint | 2 color seats

#### CONVENIENCE

Trailer connector | Adjustable & lockable steering | Cup holders  
Storage under hood | Glove compartment | Cargo bin with net  
Hitch receiver | 12V plug | Winch (3000 lbs) | Painted Half Doors

#### DURABILITY

Skid plate | Stainless steel exhaust system  
Steel bumpers | Extended fender

#### LCD DASHBOARD

Digital information center with brightness control, KM/MPH  
odometer and a multi-function gauge: RPM, speed, tachometer,  
gear position, temperature, engine light, fuel level, hour meter  
and a clock.

**PLUS VALUE OF \$2,999**

### TRANSMISSION

CV-TECH IBC dry clutch system	Primary and secondary variable transmission Gear box: L / H / N / R / P (parking lock shift system)
POWER TRAIN	2 wheel / 4 wheel drive, electric locking differential



### HEAVY DUTY REAR DIFFERENTIAL

WHEELS	
FRONT WHEELS	AT aluminum alloy (14 x 7 in)
REAR WHEELS	AT aluminum alloy (14 x 8 in)
FRONT TIRES	AT 27 x 9 x 14 (STAG 6 ply rating)
REAR TIRES	AT 27 x 11 x 14 (STAG 6 ply rating)

### SUSPENSION AND STEERING

FRONT SUSPENSION	Double wishbone independent suspension Gas shock absorber with separate adjustable rebound & compression
TRAVEL	283 mm (11.1 in)
REAR SUSPENSION	Double wishbone independent suspension Gas shock absorber with separate adjustable rebound & compression
TRAVEL	280 mm (11 in)
STEERING	Rack and pinion, Electronic Power Steering (EPS)

### Brakes

#### FRONT AND REAR BRAKE DISC SYSTEM