



2019 CFMOTO CFORCE 500 HO EPS

STARTING AT
\$7,499*

Best 5 Year
(LIMITED)
Warranty**

CFMOTO.CA



**WIND
ZONE** 
windzone.ca

*Plus PDI, freight and applicable taxes. Photos are for illustrative purposes only and any accessories shown are not included. Subject to change without notice. Details in store. **5 Year limited warranty: 1 year full + balance 48 months powertrain only or 5,000 km.



2019 CFMOTO CFORCE 500 HO EPS



**Best 5 Year
(LIMITED)
Warranty****

NEBULA BLACK RED
ORANGE TRUE TIMBER CAMO

PLUS VALUE

**GET IT ALL
THE BEST!**
PRICE, WARRANTY,
FEATURES
& ADVENTURE!

STANDARD FEATURES AND BENEFITS

SAFETY

A-arm protectors | Lateral mirrors | Horn
Halogen hi & low beam | Hazard lights | Flashers

LOOK

High quality graphics | Premium glossy paint

CONVENIENCE

Trailer connector | Double USB plug | 12V plug
Storage back driver seat | Hitch receiver | Winch (2500 lbs)

DURABILITY

Skid plate | Steel front bumper

LCD DASHBOARD

Digital information center with brightness control, KM/MPH
odometer and a multi-function gauge: RPM, speed, tachometer,
gear position, temperature, engine light, fuel level, hour meter
and a clock.

**PLUS VALUE
OF \$999**

ENGINE

TYPE	Single-Cylinder, 4-valve
DISPLACEMENT	495 cc
BORE & STROKE	91 x 76.2 mm (3.6 x 3 in)
COMPRESSION	10.3 : 1
ENGINE MANAGEMENT	BOSCH EFI & Ignition
MAXIMUM TORQUE	29.5 FT/LB @ 5800 rpm
MAXIMUM POWER OUTPUT	34.2 HP / 6200 rpm
COOLING SYSTEM	Liquid
STARTING	Electric
BATTERY	Yuasa, 30 Amp

SIZE / WEIGHT

LENGTH x WIDTH x HEIGHT	2100 x 1100 x 1150 mm (82.7 x 43.3 x 45.3 in)
WHEELBASE	1260 mm (49.6 in)
SEAT HEIGHT	540 mm (21.3 in)
GROUND CLEARANCE	250 mm (9.8 in)
FUEL TANK CAPACITY	15 L (3.96 gal)
CURB WEIGHT	345 kg (759 lbs)
TOWING CAPACITY	To come
FRONT/REAR RACK CAPACITY	20 kg (44 lb) / 40 kg (88 lbs)

TRANSMISSION

CV-TECH IBC clutch system	Primary and secondary variable transmission Gear box: L / H / N / R / P (parking lock shift system)
POWER TRAIN	2 wheel / 4 wheel drive, electric locking differential



WHEELS

FRONT WHEELS	Steel Wheels (12 x 6 in)
REAR WHEELS	Steel Wheels (12 x 7.5 in)
FRONT TIRES	AT 25 x 8-12 (Innova Mud Gear Lite 6 ply rating)
REAR TIRES	AT 25 x 10-12 (Innova Mud Gear Lite 6 ply rating)

SUSPENSION AND STEERING

FRONT SUSPENSION	Double wishbone independent suspension Hydraulic shock absorber, five adjustments spring preloads
TRAVEL	229 mm (9 in)
REAR SUSPENSION	Double wishbone independent suspension Hydraulic shock absorber, five adjustments spring preloads
TRAVEL	220 mm (8.7 in)
STEERING	Electronic Power Steering (EPS)

BRAKES

FRONT AND REAR DISC BRAKE

