



2019
CFMOTO ZFORCE 1000 EPS LX

STARTING AT
\$17,799*



Best 5 Year
(LIMITED)
Warranty**

CFMOTO.CA



**WIND
ZONE** 
windzone.ca

*Plus PDI, freight and applicable taxes. Photos are for illustrative purposes only and any accessories shown are not included. Roof accessory not included. Subject to change without notice. Details in store. **5 Year limited warranty: 1 year full + balance 48 months powertrain only or 5,000 km.



2019 CFMOTO ZFORCE 1000 EPS LX



**Best 5 Year
(LIMITED)
Warranty****

 ATHENS BLUE
 RED

PLUS VALUE

**GET IT ALL
THE BEST!**
PRICE, WARRANTY,
FEATURES
& ADVENTURE!

STANDARD FEATURES AND BENEFITS

SAFETY

Passenger hold bar | Lateral mirrors | Horn
ROPS certified Roll Cage | 4 points Seat belts | Hand brake
Halogen hi & low beam | Hazard lights | Flashers

LOOK

High quality graphics | Premium glossy paint | 2 color seats

CONVENIENCE

Trailer connector | Adjustable & lockable steering | Cup holders
Storage under hood | Glove compartment | Cargo bin with net
Hitch receiver | 12V plug | Winch (3000 lbs) | Painted Half Doors

DURABILITY

Skid plate | Stainless steel exhaust system
Steel bumpers | Extended fender

LCD DASHBOARD

Digital information center with brightness control, KM/MPH
odometer and a multi-function gauge: RPM, speed, tachometer,
gear position, temperature, engine light, fuel level, hour meter
and a clock.

**PLUS VALUE
OF \$2,999**

ENGINE

TYPE	V-Twin Cylinder, 4 strokes, 8 valves
DISPLACEMENT	962.6 cc
BORE & STROKE	91 x 74 mm (3.6 x 2.9 in)
COMPRESSION	10.6 : 1
ENGINE MANAGEMENT	BOSCH EFI and ignition system
MAXIMUM TORQUE	60.5 FT/LB @ 6200 rpm
MAXIMUM POWER OUTPUT	79 HP / 7000 rpm
COOLING SYSTEM	Liquid
STARTING	Electric
BATTERY	Yuasa, 30 Amp

SIZE / WEIGHT

LENGTH x WIDTH x HEIGHT	2870 x 1510 x 1845 mm (113 x 59.4 x 72.6 in)
WHEELBASE	2040 mm (80.3 in)
SEAT HEIGHT	395 mm (15.6 in)
GROUND CLEARANCE	310 mm (12.2 in)
FUEL TANK CAPACITY	27 L (7.1 gal)
CURB WEIGHT	610 kg (1345 lbs)
TOWING CAPACITY	To come
REAR BOX CAPACITY	100 kg (220 lbs)

TRANSMISSION

CV-TECH IBC dry clutch system	Primary and secondary variable transmission Gear box: L / H / N / R / P (parking lock shift system)
POWER TRAIN	2 wheel / 4 wheel drive, electric locking differential
HEAVY DUTY REAR DIFFERENTIAL	



WHEELS

FRONT WHEELS	AT aluminum alloy (14 x 7 in)
REAR WHEELS	AT aluminum alloy (14 x 8 in)
FRONT TIRES	AT 27 x 9 x 14 (STAG 6 ply rating)
REAR TIRES	AT 27 x 11 x 14 (STAG 6 ply rating)

SUSPENSION AND STEERING

FRONT SUSPENSION	Double wishbone independent suspension Gas shock absorber with separate adjustable rebound & compression
TRAVEL	283 mm (11.1 in)
REAR SUSPENSION	Double wishbone independent suspension Gas shock absorber with separate adjustable rebound & compression
TRAVEL	280 mm (11 in)
STEERING	Rack and pinion, Electronic Power Steering (EPS)

BRAKES

FRONT AND REAR BRAKE DISC SYSTEM

