

# 150



## ENGINE

|                             |                         |
|-----------------------------|-------------------------|
| Displacement (cc)           | 149                     |
| Engine Type                 | SOHC, 4-stroke, 2-valve |
| Bore & Stroke (mm)          | 62x49,5                 |
| Cooling System              | Air                     |
| Fuel Capacity (gal./liters) | 2.3/8.7                 |
| Alternator Capacity (amps)  | 12.5                    |
| Speedometer                 | Digital                 |
| Odometer                    | Digital                 |

## POWERTRAIN

|              |                                               |
|--------------|-----------------------------------------------|
| Transmission | Automatic CVT with Forward, Neutral & Reverse |
| Drive System | 2 WD                                          |
| Front Brakes | Drum                                          |
| Rear Brake   | Hydraulic Disc                                |

## SUSPENSION

|                       |              |
|-----------------------|--------------|
| Front Suspension      | Single A-Arm |
| Front Travel (in./cm) | 3.5/8.9      |
| Rear Suspension       | Swing Arm    |
| Rear Travel (in./cm)  | 3.5/8.9      |
| Front Tires           | 21x7-10      |
| Rear Tires            | 22x10-10     |

## COLOR

|       |
|-------|
| Black |
|-------|

## DIMENSIONS

|                           |            |
|---------------------------|------------|
| Overall Length (in./cm)   | 69.9/177.5 |
| Overall Width (in./cm)    | 37.4/95    |
| Overall Height (in./cm)   | 40.9/103.9 |
| Wheelbase (in./cm)        | 43.9/111.5 |
| Ground Clearance (in./cm) | 7.5/19.1   |
| Dry Weight (lbs./kg)      | 386/175    |

## TOWING/HAULING

|                               |         |
|-------------------------------|---------|
| Front Rack Capacity (lbs./kg) | 25/11.3 |
| Rear Rack Capacity (lbs./kg)  | 50/22.7 |
| Towing Capacity (lbs./kg)     | 300/136 |

## SUGGESTED RETAIL

|                             |
|-----------------------------|
| See your dealer for pricing |
|-----------------------------|

The minimum operator age of this vehicle is 14.

All specifications subject to change without notice.



ATVs can be hazardous to operate. For your safety always wear an approved helmet, eye protection, and protective clothing. Never engage in stunt driving; riding and alcohol/drugs don't mix and could cause serious injury or even death. Avoid excessive speeds and be particularly careful on difficult terrain. Arctic Cat recommends that all riders read and understand their operator's manual before operation. Along with concerned conservationists everywhere, Arctic Cat urges you to "Tread Lightly" on public and private lands. Ride only on designated areas or trails. Preserve your future riding opportunities by showing respect for the environment, local laws, and the rights of others when riding. Do not shoot from or lean firearms or bows against the ATV. Never carry a passenger on a single-rider ATV. **Only ride an ATV that is right for your age. Supervise riders younger than 16.** ATVs are only recommended for users over 12 years old. Arctic Cat recommends that all riders take a training course. For safety or training information in the U.S., call the ATV Safety Institute at (800) 887-2887. In Canada, call the Canada Safety Council (613) 739-1535 or see your dealer. ®™ are trademarks or registered trademarks of Arctic Cat Inc. ©2011 Arctic Cat Sales Inc., Thief River Falls, MN 56701. Arctic Cat ATVs and Side by Sides are world-class products from Arctic Cat Inc. Printed in the U.S.A.