



BEARCAT S70 XT

ENGINE

Type	2-stroke
Displacement	565 cc
Cooling	Fan
Cylinders	Twin w/push-button engine reverse
Bore x Stroke	73.8 x 66 mm
Lubrication	Oil injection
Ignition	CDI
Carburetion	2 x VM 34
Exhaust	Tuned pipe and muffler
Fuel capacity	17 gal.

POWERTRAIN

Drive clutch	Arctic 6 post (rpm sensing)
Driven clutch	10.4" dia. Arctic (roller cam)
Drive System	ACT Diamond Direct Drive
Brakes	Axial master cylinder hydraulic brake/disc on drive shaft

SUSPENSION

Front suspension	AWS VII with hydraulic twin tube shocks
Front travel	8.5 in.
Rear suspension	Articulating rear, adjustable torsion springs, 2" dia. rear-arm shock, fiberglass overload springs, Torque Sensing Link rear arm
Rear travel	13 in.

DIMENSIONS

Overall length	137 in.
Overall width	52 in.
Ski stance	40-44 in. adjustable
Runner type	Single skag w/carbide
Track type	
Track width	20 in.
Track length	154 in.
Lug	1.375 in.
Pitch	2.86 in.

COLORS

Blue

STANDARD FEATURES

Electric start, high-height windshield, digital/analog gauge, electric gas gauge, clock, low oil light, high/low hand & thumb warmers, detachable passenger seat, wind deflectors, tunnel rails, mountain strap, hitch

OPTIONAL FEATURES

Cargo rack, front & rear receiver bumpers, gear bag, 3rd seat, light bar, safety beacon, receiver hitch, 12-in. ski skins, side rails, snowplow, winch, extreme high windshield

SUGGESTED RETAIL

See your dealer for pricing.



©2011 Arctic Cat Inc. All rights reserved. ®™ and the Arctic Cat logo are trademarks of Arctic Cat Inc. Because of our ongoing commitment to product quality and innovation, Arctic Cat reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. See your dealer for details.