



BEARCAT Z1 XT

ENGINE

Type	4-stroke
Displacement	1056 cc
Cooling	Liquid
Cylinders	Twin w/push-button reverse
Bore x Stroke	98 x 70 mm
Lubrication	Dry sump
Ignition	Full transistor/coil at plug
Carburetion	48 mm dual throttle body EFI
Exhaust	Stainless steel muffler
Fuel capacity	17 gal.

POWERTRAIN

Drive clutch	Arctic 6 post (rpm sensing)
Driven clutch	10.4" dia. Arctic (roller cam)
Drive System	ACT Diamond Direct Drive
Brakes	Axial master cylinder hydraulic brake/disc on drive shaft

SUSPENSION

Front suspension	AWS VII with hydraulic twin tube shocks
Front travel	8.5 in.
Rear suspension	Articulating rear, adjustable torsion springs, 2" dia. rear-arm shock, fiberglass overload springs, Torque Sensing Link rear arm
Rear travel	13 in.

DIMENSIONS

Overall length	137 in.
Overall width	52 in.
Ski stance	40-44 in. adjustable
Runner type	Dual skag w/carbide
Track type	
Track width	20 in.
Track length	154 in.
Lug	1.375 in.
Pitch	2.86 in.

COLORS

Blue or Green

STANDARD FEATURES

Electric start, high-height windshield, digital/analog gauge, electric gas gauge, clock, low oil pressure light, high/low hand & thumb warmers, detachable passenger seat, wind deflectors, tunnel rails, mountain strap, hitch, mirrors, accessory outlet

OPTIONAL FEATURES

Cargo rack, engine heater, front & rear receiver bumpers, gear bag, heated driver & passenger seats, 3rd seat, light bar, safety beacon, passenger hand warmers, radiator, receiver hitch, remote electric start, 12-in. ski skins, side rails, snowplow, winch, extreme high windshield

SUGGESTED RETAIL

See your dealer for pricing.



©2011 Arctic Cat Inc. All rights reserved. ®™ and the Arctic Cat logo are trademarks of Arctic Cat Inc. Because of our ongoing commitment to product quality and innovation, Arctic Cat reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. See your dealer for details.