



PROCROSS F 1100 LXR

ENGINE

Type	4-stroke
Displacement	1056 cc
Cooling	Liquid
Cylinders	Twin w/push-button reverse
Bore x Stroke	98 x 70 mm
Lubrication	Dry sump
Ignition	Full transistor/coil at plug
Carburetion	48 mm dual throttle body EFI
Exhaust	Stainless steel muffler
Fuel capacity	10.6 gal.

POWERTRAIN

Drive clutch	Arctic 6 post (rpm sensing)
Driven clutch	10.75" dia. Arctic (roller cam)
Drive System	Arctic Drive System
Brakes	Radial master cylinder hydraulic brake/disc on drive shaft

SUSPENSION

Front suspension	Arctic Race Suspension with FOX Zero Pro (IFP) shocks and sway bar
Front travel	10 in.
Rear suspension	FasTrack slide-action suspension with Tri-hub rear axle system, coupling blocks, torque sensing link, adjustable torsion springs, FOX (IFP) shocks
Rear travel	13.5 in.

DIMENSIONS

Overall length	118 in.
Overall width	48 in.
Ski stance	42-43 in. adjustable
Runner type	Dual skag w/carbide
Track type	HackSaw
Track width	15 in.
Track length	128 in.
Lug	1.0 in.
Pitch	2.52 in.

COLORS

Black or Green

STANDARD FEATURES

Front bumper, electric start, heated seat, adjustable handlebar, mid-height windshield, deluxe digital/analog gauge, electric gas gauge, low oil pressure light, coolant overheat light, clock, accessory outlet, high/low hand warmer, high/low thumb warmer, rear storage bag

OPTIONAL FEATURES

Front sport bumper, engine heater, hand guards, hitch, rack, premium shocks, 2-up seat, storage bags, tank pads, tether switch, (ex low, flyscreen, low, mid, high) windshield

SUGGESTED RETAIL

See your dealer for pricing.



©2011 Arctic Cat Inc. All rights reserved. ®™ and the Arctic Cat logo are trademarks of Arctic Cat Inc. Because of our ongoing commitment to product quality and innovation, Arctic Cat reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. See your dealer for details.