



FS70

ENGINE

Type	2-stroke
Displacement	565 cc
Cooling	Fan
Cylinders	Twin w/push-button engine reverse
Bore x Stroke	73.8 x 66 mm
Lubrication	Oil injection
Ignition	CDI
Carburetion	2 x VM 34
Exhaust	Tuned pipe and muffler
Fuel capacity	10.8 gal.

POWERTRAIN

Drive clutch	Arctic 6 post (rpm sensing)
Driven clutch	10.4" dia. Arctic (roller cam)
Drive System	ACT Diamond Direct Drive
Brakes	Axial master cylinder hydraulic brake/disc on drive shaft

SUSPENSION

Front suspension	AWS VII with hydraulic twin tube shocks and sway bar
Front travel	9.5 in.
Rear suspension	FasTrack slide-action suspension, adjustable torsion springs, hydraulic twin tube shocks
Rear travel	13.5 in.

DIMENSIONS

Overall length	118 in.
Overall width	48 in.
Ski stance	43 in.
Runner type	Single skag w/carbide
Track type	
Track width	15 in.
Track length	128 in.
Lug	1.0 in.
Pitch	2.52 in.

COLORS

Green or Orange

STANDARD FEATURES

Electric start, mid-height windshield, digital/analog gauge, electric gas gauge, low oil light, high/low hand warmer, high/low thumb warmer

OPTIONAL FEATURES

Front sport bumper, hand guards, hitch, mirrors, rack, 2-up seat, storage bags, tether switch, (flyscreen, low, ex high) windshield

SUGGESTED RETAIL

See your dealer for pricing.



©2011 Arctic Cat Inc. All rights reserved. ®™ and the Arctic Cat logo are trademarks of Arctic Cat Inc. Because of our ongoing commitment to product quality and innovation, Arctic Cat reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. See your dealer for details.