



PROCROSS F 800 SNO PRO

ENGINE

Type	2-stroke
Displacement	794 cc
Cooling	Liquid
Cylinders	Twin w/push-button engine reverse
Bore x Stroke	85 x 70 mm
Lubrication	Oil injection
Ignition	3D
Carburetion	46 mm dual throttle body batteryless EFI
Exhaust	APV with tuned pipe, pipe sensor and stainless steel muffler
Fuel capacity	10.6 gal.

POWERTRAIN

Drive clutch	Arctic 6 post (rpm sensing)
Driven clutch	10.75" dia. Arctic (roller cam)
Drive System	Arctic Drive System
Brakes	Radial master cylinder hydraulic brake/disc on drive shaft

SUSPENSION

Front suspension	Arctic Race Suspension with FOX Float 2 shocks and sway bar
Front travel	10 in.
Rear suspension	FasTrack slide-action suspension with Tri-hub rear axle system, couple blocks, torque sensing link, adjustable torsion springs, FOX (IFP) shocks (2" dia. rear shock)
Rear travel	13.5 in.

DIMENSIONS

Overall length	118 in.
Overall width	48 in.
Ski stance	42-43 in. adjustable
Runner type	Single skag w/carbide
Track type	RipSaw
Track width	15 in.
Track length	128 in.
Lug	1.25 in.
Pitch	2.52 in.

COLORS

Green or Orange

STANDARD FEATURES

Front bumper, adjustable handlebar, low-height windshield, deluxe digital/analog gauge, electric gas gauge, low oil light, coolant overheat light, accessory outlet, high/low hand warmer, high/low thumb warmer

OPTIONAL FEATURES

Front sport bumper, hand guards, hitch, rack, premium shocks, 2-up seat, storage bags, tank pads, tether switch, (ex low, flyscreen, low, mid, high) windshield

SUGGESTED RETAIL

See your dealer for pricing.



©2011 Arctic Cat Inc. All rights reserved. ®™ and the Arctic Cat logo are trademarks of Arctic Cat Inc. Because of our ongoing commitment to product quality and innovation, Arctic Cat reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. See your dealer for details.