



PROCLIMB M 800 SNO PRO

ENGINE

Type	2-stroke
Displacement	794 cc
Cooling	Liquid
Cylinders	Twin w/push-button engine reverse
Bore x Stroke	85 x 70 mm
Lubrication	Oil injection
Ignition	3D
Carburetion	46 mm dual throttle body batteryless EFI
Exhaust	APV with tuned pipe, pipe sensor and stainless steel muffler
Fuel capacity	10.6 gal.

POWERTRAIN

Drive clutch	Arctic 6 post (rpm sensing)
Driven clutch	10.75" dia. Arctic (roller cam)
Drive System	Arctic Drive System
Brakes	Radial master cylinder hydraulic brake/disc on drive shaft

SUSPENSION

Front suspension	Arctic Race Suspension with FOX Float 2 shocks
Front travel	9 in.
Rear suspension	M rear suspension with Tri-hub rear axle system, FOX Zero Pro (IFP) shock on front arm, FOX Float 2 shock on rear arm
Rear travel	15.5 in. (153)/16.5 in. (162)

DIMENSIONS

Overall length	125 in. (153)/130 in. (162)
Overall width	46 in.
Ski stance	40-41 in. adjustable
Runner type	Single skag w/carbide
Track type	Power Claw
Track width	15 in.
Track length	153 in. & 162 in.
Lug	2.25 in.
Pitch	3.0 in.

COLORS

Green or Orange

STANDARD FEATURES

Front bumper, telescoping handlebar, low-height windshield, deluxe digital/analog gauge, electric gas gauge, low oil light, coolant overheat light, accessory outlet, high/low hand & thumb warmers

OPTIONAL FEATURES

Electric start, front sport bumper, goggle holder, hand guards, hitch, ice scratchers, rack, premium shocks, storage bags, tank pads, tether switch, vented panels, (ex low, flyscreen, low, mid, high) windshield

SUGGESTED RETAIL

See your dealer for pricing.



©2011 Arctic Cat Inc. All rights reserved. ®™ and the Arctic Cat logo are trademarks of Arctic Cat Inc. Because of our ongoing commitment to product quality and innovation, Arctic Cat reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. See your dealer for details.