



PROCLIMB M 1100 TURBO SNO PRO 50TH

ENGINE

Type	4-stroke
Displacement	1056 cc
Cooling	Liquid
Cylinders	Twin w/push-button reverse
Bore x Stroke	98 x 70 mm
Lubrication	Dry sump
Ignition	Full transistor
Carburetion	46 mm single throttle body EFI
Exhaust	Turbocharger with stainless steel muffler
Fuel capacity	10.6 gal.

POWERTRAIN

Drive clutch	Arctic 6 post (rpm sensing)
Driven clutch	10.75" dia. Arctic (roller cam)
Drive System	Arctic Drive System
Brakes	Radial master cylinder hydraulic brake/disc on drive shaft

SUSPENSION

Front suspension	Arctic Race Suspension with FOX Float 2 shocks
Front travel	9 in.
Rear suspension	M rear suspension with Tri-hub rear axle system, FOX Zero Pro (IFP) shock on front arm, FOX Float 2 shock on rear arm
Rear travel	16.5 in.

DIMENSIONS

Overall length	130 in.
Overall width	46 in.
Ski stance	40-41 in. adjustable
Runner type	Single skag w/carbide
Track type	Power Claw
Track width	15 in.
Track length	162 in.
Lug	2.25 in.
Pitch	3.0 in.

COLORS

50th Anniversary Black

STANDARD FEATURES

Front bumper, electric start, low-height windshield, deluxe digital/analog gauge, electric gas gauge, low oil pressure light, coolant overheat light, clock, accessory outlet, high/low hand & thumb warmers, heated seat, front sport bumper, ice scratchers

OPTIONAL FEATURES

Engine heater, goggle holder, hand guards, hitch, rack, premium shocks, heated seat, storage bags, tank pads, tether switch, vented panels, (ex low, flyscreen, low, mid, high) windshield

SUGGESTED RETAIL

See your dealer for pricing.



©2011 Arctic Cat Inc. All rights reserved. ®™ and the Arctic Cat logo are trademarks of Arctic Cat Inc. Because of our ongoing commitment to product quality and innovation, Arctic Cat reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. See your dealer for details.