

## HSS1332TCD

- All-new full featured, track drive, 2 stage snowblower with improved Honda performance and durability
- 81.0 cm (31.9 in) clearing width / 51 cm (20 in.) clearing height
- Moves up to 65 metric tons of snow per hour with a discharge distance up to 17 metres (56 ft.)
- Residential or Commercial snow removal



### SPECIFICATIONS

<b>Axle Type</b>	Track drive	<b>Clearing Snow Volume Capacity *</b>	Up to 65 metric tons (72 tons/hr)
<b>Drive Type</b>	Hydrostatic transmission (HST)	<b>Engine Type</b>	4-stroke, OHV, single cylinder
<b>Transmission Oil Capacity</b>	0.75 Litre (26.4 fl. Imp. oz)	<b>Honda Engine Model</b>	GX390T2
<b>Recommended Oil</b>	Honda hydrostatic transmission fluid	<b>Displacement</b>	389 cc (23.7 CID)
<b>Speeds</b>	Infinitely variable	<b>Ignition System</b>	CDI magneto
<b>Maximum Ground Speed</b>	Forward : 59.4 m/min. (194.9 ft./min) Reverse : 40.8 m/min. (133.9 ft./min)	<b>Recoil Starter</b>	Standard (Back-up)
<b>Clearing Width</b>	81.0 cm (31.9 in)	<b>Electric Starter</b>	Standard 12 VDC type
<b>Intake Housing Height</b>	51.0 cm (20.1 in)	<b>Lubrication System</b>	Forced splash
<b>Auger Diameter</b>	35.5 cm (14.0 in)	<b>Oil Capacity</b>	1.1 Litre (38.7 fl. Imp. oz)
<b>Auger Type</b>	Steel serrated (Spiral)	<b>Recommended Oil</b>	SAE 5W30 API service classification SJ or later
<b>Auger Drive</b>	Belt driven shaft	<b>Fuel Capacity</b>	5.7 Litres (1.25 Imp. gal)
<b>Auger Transmission</b>	Screw gear	<b>Recommended Fuel</b>	Unleaded gasoline (Pump octane rating 86 or higher)
<b>Auger Oil Capacity</b>	0.18 Litre (6.3 fl. Imp. oz)	<b>Operational Time per Tankful **</b>	1.8 hours
<b>Recommended Oil</b>	SAE 80W90 GL-5	<b>Wheel/Tire Size</b>	N/A
<b>Auger Height Adjustment</b>	Gas assist	<b>Overall Length</b>	146.5 cm (57.7 in)
<b>Chute Rotation</b>	Remote electric Joystick control	<b>Overall Width</b>	82.5 cm (32.5 in)
<b>Chute Turning Radius</b>	187°	<b>Overall Height</b>	117.0 cm (46.1 in)
<b>Deflection Control</b>	Remote electric Joystick control	<b>Dry Weight</b>	130.0 kg (286.6 lb)
<b>Chute Material</b>	Steel	<b>Lighting Coil</b>	Standard
<b>Maximum Throw Distance *</b>	17 m (56 ft)	<b>WorkLight</b>	Standard
		<b>Warranty</b>	36-month, non-commercial use / 36-month, commercial use distributor's warranty

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice. See your Honda Power Equipment dealer for details.

For optimum performance and safety, please read your owner's manual before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.

©TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.