

HSM1336iKC Hybrid

- Hybrid drive, dual stage snowblower with i-
Control computerized control system
- 92.0 cm (36.2 in) clearing width / 58.0 cm (22.8
in) clearing height
- Moves up to 83 metric tons of snow per hour with
a discharge distance up to 19 m (62.3 ft)
- Residential or Commercial snow removal



SPECIFICATIONS

Axle Type	Track drive	Clearing Snow Volume Capacity (Approximate) *	up to 83 metric tons (91 tons/hr)
Drive Type	Electric i-Control (24 VDC drive motors)	Engine Type	4-stroke, OHV, single cylinder
Transmission Oil Capacity	0.3 Litre (10.6 fl. Imp. oz)	Honda Engine Model	i-GX390T2
Recommended Oil	SAE 5W30 API service classification SJ or later	Displacement	389 cc (23.7 CID)
Speeds	Infinitely variable (Load control)	Ignition System	CDI magneto
Maximum Ground Speed	Forward : 50.0 m/min. (164.0 ft./min) Reverse : 35.0 m/min. (114.8 ft./min)	Recoil Starter	N/A
Clearing Width	92.0 cm (36.2 in)	Electric Starter	Standard 24 VDC type
Intake Housing Height	58.0 cm (22.8 in)	Lubrication System	Forced splash
Auger Diameter	39.8 cm (15.7 in)	Oil Capacity	1.1 Litre (38.7 fl. Imp. oz)
Auger Type	Steel serrated (Spiral)	Recommended Oil	SAE 5W30 API service classification SJ or later
Auger Drive	Belt driven shaft, electromagnetic clutch	Fuel Capacity	5.7 Litres (1.25 Imp. gal)
Auger Transmission	Worm gear	Recommended Fuel	Unleaded gasoline (Pump octane rating 86 or higher)
Auger Oil Capacity	0.2 Litre (7.0 fl. Imp. oz)	Operational Time per Tankful **	1.6 hours
Recommended Oil	SAE #90 gear oil	Wheel/Tire Size	N/A
Auger Height Adjustment	Electric auger-height adjuster (Automatic raise at return path)	Overall Length	176.0 cm (69.3 in)
Chute Rotation	Remote electric "Joystick" control	Overall Width	92.0 cm (36.2 in)
Chute Turning Radius	240°	Overall Height	134.0 cm (52.8 in)
Deflection Control	Remote electric "Joystick" control	Dry Weight	240 kg (529.1 lb)
Chute Material	Steel	Lighting Coil	Standard
Maximum Throw Distance *	19 m (62.3 ft)	Work Light	Standard (24 VDC, 40 watt)
		Warranty	36-month, non-commercial use / 36-month, commercial use distributor's warranty

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice. See your Honda Power Equipment dealer for details.

For optimum performance and safety, please read your owner's manual before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.

©TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.