

EB10000C

- 1 10,000 watts of power with dual-voltage configuration and full ground fault circuit interrupter (GFCI) protection
- 1 Convenient 12 VDC electric start (battery included)
- 1 Best fuel efficiency and lowest noise rating in its class



SPECIFICATIONS

MAXIMUM AC OUTPUT (WATTS)	10000	FUEL TANK CAPACITY (LITRES)	31 litres (6.82 Imp. gal)
AC Voltage Available	120/240	TRANSPORT WHEELS	2 Wheel standard
MAXIMUM CONTINUOUS AC OUTPUT (WATTS)	9000	LIFTING HOOK	Standard
Max. Rated AC Amperage @ 120 V/240 V	37.5 x 2 (75.0/37.5)	BATTERY	Standard
GROUND FAULT CIRCUIT INTERRUPTER (GFCI)	Standard	Approximate Running Time/Tankful (hrs)	6.5**
FREQUENCY (HERTZ)	60	Rated Fuel Consumption (Litres/Hour)	4.77**
AUTOMATIC VOLTAGE REGULATOR	Standard DAVR (Digital Automatic Voltage Regulator)	Noise Level dB(A) (1.5 m to 7 m)	72**
DC Output Volts/Amps	N/A	Length (Without Handles and Wheels)	973 mm (38.3 in.)
Engine Type	Honda GX630H OHV, 90° V-Twin design, 4-stroke, air-cooled	Length (With Handles and Wheels)	1,420 mm (55.9 in.)
DISPLACEMENT	688 cc	Width (Without Handles and Wheels)	552 mm (21.7 in.)
STARTING SYSTEM	Electric	Width (With Handles and Wheels)	703 mm (27.7 in.)
Low Level Oil Alert System	Standard	Height (Without Lift-Hook)	695 mm (27.4 in.)
AUTO THROTTLE	Standard	Height (With Lift-Hook)	891 mm (35.1 in.) standard
REMOTE START CAPABILITY	No	DRY WEIGHT	183.0 kg (403.4 lb) including battery
REMOTE START KIT PART NUMBER INFO	N/A	COLD CLIMATE TECHNOLOGY	Standard

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice. See your Honda Power Equipment dealer for details.

For optimum performance and safety, please read your owner's manual before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.

®/TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.