

## EM6500S2C

- Portable power with premium features and traditional Honda durability and performance
- 6500 watts maximum AC output
- Home backup and Commercial usage (for non-GFCI applications)
- Suitable for rental applications



### SPECIFICATIONS

<b>MAXIMUM AC OUTPUT (WATTS)</b>	6500	<b>FUEL TANK CAPACITY (LITRES)</b>	23.5
<b>AC Voltage Available</b>	120/240	<b>TRANSPORT WHEELS</b>	2 Wheel standard
<b>MAXIMUM CONTINUOUS AC OUTPUT (WATTS)</b>	5,500 7,000 (iAVR)	<b>LIFTING HOOK</b>	Optional (P/N 06810-Z22-A30ZA)
<b>Max. Rated AC Amperage @ 120 V/240 V</b>	45.8/22.9 (58.3/29.2 for 10 sec. iAVR)	<b>BATTERY</b>	Standard (P/N 31500-MCR-J01)
<b>GROUND FAULT CIRCUIT INTERRUPTER (GFCI)</b>	-	<b>Approximate Running Time/Tankful (hrs)</b>	6.9** / 10.4***
<b>FREQUENCY (HERTZ)</b>	60	<b>Rated Fuel Consumption (Litres/Hour)</b>	3.40**
<b>AUTOMATIC VOLTAGE REGULATOR</b>	Standard iAVR (Intelligent Automatic Voltage Regulator)	<b>Noise Level dB(A) (1.5 m to 7 m)</b>	73**
<b>DC Output Volts/Amps</b>	12/8.0	<b>Length (Without Handles and Wheels)</b>	681 mm (26.8 in.)
<b>Engine Type</b>	Honda iGX390T2 OHV, 4-stroke, air-cooled	<b>Length (With Handles and Wheels)</b>	1,051 mm (41.4 in.)
<b>DISPLACEMENT</b>	389 cc	<b>Width (Without Handles and Wheels)</b>	530 mm (20.9 in.)
<b>STARTING SYSTEM</b>	Electric/recoil	<b>Width (With Handles and Wheels)</b>	706 mm (27.8 in.)
<b>Low Level Oil Alert System</b>	Standard	<b>Height (Without Lift-Hook)</b>	719 mm (28.3 in.)
<b>AUTO THROTTLE</b>	Standard	<b>Height (With Lift-Hook)</b>	773 mm (30.4 in.) Optional lift hook
<b>REMOTE START CAPABILITY</b>	Optional	<b>DRY WEIGHT</b>	104.8 kg (231.0 lb.)
<b>REMOTE START KIT PART NUMBER INFO</b>	06610-Z22-800ZA (10M)	<b>COLD CLIMATE TECHNOLOGY</b>	Standard
		<b>Common Duplex Receptacle Specifications</b>	40 amps/120 VAC continuous is available as combined total from these twin duplex AC receptacles. Maximum of 20 amps available from each GFCI duplex receptacle.

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice. See your Honda Power Equipment dealer for details.

For optimum performance and safety, please read your owner's manual before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.

©TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.