

HS621K2C



- 1 Single-stage, semi-self propelled, clears a 21 in/53 cm width
- 1 Honda GX160T2, OHV, 4-stroke engine
- 1 Auger-assisted forward drive
- 1 Residential snow removal



SPECIFICATIONS

Discharge Type	Single stage
Axle Type	Wheel
Drive Type	Auger assist
Speeds	N/A
Maximum Ground Speed	N/A
Clearing Width	52.2 cm (20.6 in)
Intake Housing Height	32.5 cm (12.8 in)
Auger Diameter	23.0 cm (9.1 in)
Auger Type	Rubber edge
Auger Drive	Belt
Auger Height Adjustment	Scraper bar
Chute Rotation	Manual lever
Chute Turning Radius	220 degrees
Deflection Control	Manual lever
Chute Material	Steel
Maximum Throw Distance ¹	10 m (33 ft)

Clearing Snow Volume Capacity (Approximate) ¹	Up to 33 metric tons/hr (36 tons/hr)
Engine Type	4-stroke; OHV; single cylinder
Honda Engine Model	GX160T2
Displacement	163 cc (10.0 CID)
Ignition System	Transistorized
Recoil Starter	Standard
Electric Starter	N/A
Lubrication System	Forced splash
Oil Capacity	0.58 Litre (20.4 fl. Imp. oz)
Recommended Fuel	Regular unleaded gasoline (87 Octane)
Fuel Capacity	1.4 Litre (31.0 fl. Imp. oz)
Operational Time per Tankful ²	1.6 hour
Wheel/Tire Size	17.5 cm (6.9 in.)
Overall Length	123.0 cm (48.4 in)
Overall Width	57.0 cm (22.4 in)
Overall Height	98.0 cm (38.6 in)
Dry Weight	41.0 kg (90.4 lb)

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice.
See your Honda Power Equipment dealer for details.

For optimum performance and safety, please read your owner's manual before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.

®/TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.