

HS621K2CS

- Single-stage, semi-self propelled, clears a 21 in/53 cm width
- Honda GX160T2, OHV, 4-stroke engine
- Auger-assisted forward drive
- Residential snow removal



SPECIFICATIONS

Discharge Type	Single stage	Clearing Snow Volume Capacity (Approximate) ¹	Up to 33 metric tons/hr (36 tons/hr)
Axle Type	Wheel	Engine Type	4-stroke; OHV; single cylinder
Drive Type	Auger assist	Honda Engine Model	GX160T2
Speeds	N/A	Displacement	163 cc (10.0 CID)
Maximum Ground Speed	N/A	Ignition System	Transistorized
Clearing Width	52.2 cm (20.6 in)	Recoil Starter	Standard (Back-up)
Intake Housing Height	32.5 cm (12.8 in)	Electric Starter	Standard 120 VAC type
Auger Diameter	23.0 cm (9.1 in)	Lubrication System	Forced splash
Auger Type	Rubber edge	Oil Capacity	0.58 Litre (20.4 fl. Imp. oz)
Auger Drive	Belt	Recommended Fuel	Regular unleaded gasoline (87 Octane)
Auger Height Adjustment	Scraper bar	Fuel Capacity	1.4 Litre (31.0 fl. Imp. oz)
Chute Rotation	Manual lever	Operational Time per Tankful ²	1.6 hour
Chute Turning Radius	220 degrees	Wheel/Tire Size	17.5 cm (6.9 in.)
Deflection Control	Manual lever	Overall Length	123.0 cm (48.4 in)
Chute Material	Steel	Overall Width	57.0 cm (22.4 in)
Maximum Throw Distance ¹	10 m (33 ft)	Overall Height	98.0 cm (38.6 in)
		Dry Weight	44.0 kg (97 lb)

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice. See your Honda Power Equipment dealer for details.

For optimum performance and safety, please read your owner's manual before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.

®/TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.