

# HSS622TC

- Dual-stage, track drive, clears a 22 in/56 cm width
- Honda GX160T2, OHV, 4-stroke engine
- 2-speed forward transmission plus reverse
- Residential snow removal



## SPECIFICATIONS

Discharge Type	Dual stage	Clearing Snow Volume Capacity (Approximate) <sup>1</sup>	Up to 37 metric tons/hr (41 tons/hr)
Axle Type	Track drive	Engine Type	4-stroke; OHV; single cylinder
Drive Type	Gear mesh transmission	Honda Engine Model	GX160T2
Speeds	2 forward / 1 reverse	Displacement	163 cc (10.0 CID)
Maximum Ground Speed	1: 11.4 m/min. (37.4 ft/min) 2: 28.2 m/min. (92.5 ft/min) R: 28.2 m/min. (92.5 ft/min)	Ignition System	Transistorized
Clearing Width	55.0 cm (21.7 in)	Recoil Starter	Standard
Intake Housing Height	42.0 cm (16.5 in)	Electric Starter	N/A
Auger Diameter	30.5 cm (12.0 in)	Lubrication System	Forced splash
Auger Type	Steel	Oil Capacity	0.58 Litre (20.4 fl. Imp. oz)
Auger Drive	Dry; multi-disc clutch	Recommended Fuel	Regular unleaded gasoline (87 Octane)
Auger Height Adjustment	3 position adjuster	Fuel Capacity	3.1 Litres (0.68 Imp. gal)
Chute Rotation	Manual lever	Operational Time per Tankful <sup>2</sup>	2.7 hours
Chute Turning Radius	195 degrees	Wheel/Tire Size	N/A
Deflection Control	Manual lever	Overall Length	149.0 cm (58.7 in)
Chute Material	Steel	Overall Width	55.0 cm (21.7 in)
Maximum Throw Distance <sup>1</sup>	14 m (46 ft)	Overall Height	112.5 cm (44.3 in)
		Dry Weight	65.0 kg (143.3 lb)

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice.

See your Honda Power Equipment dealer for details.

For optimum performance and safety, please read your owner's manual before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.

®/TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.