

HSS622TCS

- 1 Dual-stage, track drive, clears a 22 in/56 cm width
- 1 Honda GX160T2, OHV, 4-stroke engine
- 1 2-speed forward transmission plus reverse
- 1 Residential or Commercial snow removal



SPECIFICATIONS

Discharge Type	Dual stage	
Axle Type	Track drive	Clearing Snow Volume Capacity (Approximate)¹ Up to 37 metric tons/hr (41 tons/hr)
Drive Type	Gear mesh transmission	Engine Type 4-stroke; OHV; single cylinder
Speeds	2 forward / 1 reverse	Honda Engine Model GX160T2
Maximum Ground Speed	1: 11.4 m/min. (37.4 ft./min) 2: 28.2 m/min. (92.5 ft./min) R: 28.2 m/min. (92.5 ft./min)	Displacement 163 cc (10.0 CID)
Clearing Width	55.0 cm (21.7 in)	Ignition System Transistorized
Intake Housing Height	42.0 cm (16.5 in)	Recoil Starter Standard (Back-up)
Auger Diameter	30.5 cm (12.0 in)	Electric Starter Standard 120 VAC type
Auger Type	Steel	Lubrication System Forced splash
Auger Drive	Dry; multi-disc clutch	Oil Capacity 0.58 Litre (20.4 fl. Imp. oz)
Auger Height Adjustment	3 position adjuster	Recommended Fuel Regular unleaded gasoline (87 Octane)
Chute Rotation	Manual lever	Fuel Capacity 3.1 Litres (0.68 Imp. gal)
Chute Turning Radius	195 degrees	Operational Time per Tankful² 2.7 hours
Deflection Control	Manual lever	Wheel/Tire Size N/A
Chute Material	Steel	Overall Length 149.0 cm (58.7 in)
Maximum Throw Distance¹	14 m (46 ft)	Overall Width 55.0 cm (21.7 in)
		Overall Height 112.5 cm (44.3 in)
		Dry Weight 70.0 kg (154.3 lb)

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice. See your Honda Power Equipment dealer for details.

For optimum performance and safety, please read your owner's manual before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.

®/TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.