

HSS724TC



- 1 Dual-stage, track drive, clears a 24 in/61 cm width
- 1 Honda GX200T2, OHV, 4-stroke engine
- 1 Variable speed hydrostatic transmission
- 1 Residential or Commercial snow removal



SPECIFICATIONS

Discharge Type	Dual stage
Axle Type	Track drive
Drive Type	Hydrostatic transmission
Speeds	Infinitely variable
Maximum Ground Speed	Forward: 54.0 m/min. (177.2 ft./min) Reverse: 40.8 m/min. (133.8 ft./min)
Clearing Width	60.5 cm (23.8 in)
Intake Housing Height	42.0 cm (16.5 in)
Auger Diameter	30.5 cm (12.0 in)
Auger Type	Steel serrated
Auger Drive	Belt driven shaft
Auger Height Adjustment	Gas assist
Chute Rotation	Remote manual crank
Chute Turning Radius	210 degrees
Deflection Control	Remote manual lever
Chute Material	Steel
Maximum Throw Distance ¹	14 m (46 ft)

Clearing Snow Volume Capacity (Approximate) ¹	Up to 42 metric tons/hr (46 tons/hr)
Engine Type	4-stroke; OHV; single cylinder
Honda Engine Model	GX200T2
Displacement	196 cc (12.0 CID)
Ignition System	Transistorized
Recoil Starter	Standard
Electric Starter	N/A
Lubrication System	Forced splash
Oil Capacity	0.60 Litre (21.1 fl. Imp. oz)
Recommended Fuel	Regular unleaded gasoline (87 Octane)
Fuel Capacity	3.1 Litres (0.68 Imp. gal)
Operational Time per Tankful 2	2 hours
Wheel/Tire Size	N/A
Overall Length	139.0 cm (54.7 in)
Overall Width	62.0 cm (24.4 in)
Overall Height	107.5 cm (42.3 in)
Dry Weight	90.0 kg (198.4 lb)

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice.
See your Honda Power Equipment dealer for details.

For optimum performance and safety, please read your owner's manual before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.

®/TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.