

HSS724TCD

- 1 Dual-stage, track drive, clears a 24 in/61 cm width
- 1 Honda GX200T2, OHV, 4-stroke engine
- 1 Variable speed hydrostatic transmission
- 1 Residential or Commercial snow removal



SPECIFICATIONS

Discharge Type	Dual stage	Clearing Snow Volume Capacity (Approximate)¹	Up to 42 metric tons/hr (46 tons/hr)
Axle Type	Track drive	Engine Type	4-stroke; OHV; single cylinder
Drive Type	Hydrostatic transmission	Honda Engine Model	GX200T2
Speeds	Infinitely variable	Displacement	196 cc (12.0 CID)
Maximum Ground Speed	Forward: 54.0 m/min. (177.2 ft./min) Reverse: 40.8 m/min. (133.8 ft./min)	Ignition System	Transistorized
Clearing Width	60.5 cm (23.8 in)	Recoil Starter	Standard (Back-up)
Intake Housing Height	42.0 cm (16.5 in)	Electric Starter	Standard 12 VDC type
Auger Diameter	30.5 cm (12.0 in)	Lubrication System	Forced splash
Auger Type	Steel serrated	Oil Capacity	0.60 Litre (21.1 fl. Imp. oz)
Auger Drive	Belt driven shaft	Recommended Fuel	Regular unleaded gasoline (87 Octane)
Auger Height Adjustment	Gas assist	Fuel Capacity	3.10 Litres (0.68 Imp. gal)
Chute Rotation	Remote electric "Joystick" control	Operational Time per Tankful²	2 hours
Chute Turning Radius	210 degrees	Wheel/Tire Size	N/A
Deflection Control	Remote electric "Joystick" control	Overall Length	139.0 cm (54.7 in)
Chute Material	Steel	Overall Width	62.0 cm (24.4 in)
Maximum Throw Distance¹	14 m (46 ft)	Overall Height	107.5 cm (42.3 in)
		Dry Weight	99.0 kg (218.3 lb)

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice. See your Honda Power Equipment dealer for details.

For optimum performance and safety, please read your owner's manual before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.

®/TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.