




323R

Our lightest brushcutter. A versatile model for a variety of tasks, from light edge trimming to clearing thicker grass. Angled handle bar and combi guard for both trimmer heads and grass blades. Ergonomic and comfortable harness.



SMART START®

The engine and starter have been designed so the machine starts quickly with minimum effort. Resistance in the starter cord is reduced by up to 40%.



AUTO RETURN STOP SWITCH

When the machine is turned off, the stop button automatically returns to start position for trouble free start.



FUEL PUMP

Fuel pump designed for easy starting.



STANDARD DOUBLE HARNESS

Standard harness for lighter brushcutters.

Features

- Grass bevel gear for best cutting performance

Technical data

Cylinder displacement	1.5 cu.inch / 24.5 cm ³
Power output	1.2 hp / 0.9 kW
Maximum power speed	9000 rpm
Fuel tank volume	16.91 fl oz / 0.5 lit
Fuel consumption	600 g/kWh
Fuel consumption	1.19 lbs/h / 0.55 kg/h
Idling speed	2700 rpm
Spark plug	Champion RCJ7Y, NGK BPMR7A
Electrode gap	0.02" / 0.5 mm
Torque, max.	1.1 Nm / 6600 rpm
Clutch engagement speed	3800 rpm (± 120 rpm)
Lubricant type	Husqvarna or equiv. at 50:1
Maximum rpm output shaft	9200 rpm
Output shaft thread	M10x1.25V
Lubricant type (bevel gear)	Biodegradable grease
Equivalent vibration level (ahv, eq) left / right handle	3/4 m/s ²
Sound pressure level at operators ear	97 dB(A)
Sound power level, guaranteed (LWA)	110 dB(A)
Gear ratio	1:1.46
Drive gear angle	30 °
OEM Trimmer head	—
OEM Grass blade	Grass 255-4
OEM Harness	Standard double harness
Weight (excl. cutting equipment)	10 lbs / 4.5 kg
Tube length	58.39 inch / 1483 mm
Tube diameter	0.94" / 24 mm

ARTICLES

968 04 75-02 T35 + Grass 255-4 (1"), USA

