



## YTA19K42

Husqvarna tractors offer premium performance with quality results. Their compact size makes them easy to manoeuvre and require less space for storage. Features such as fender-mounted cutting height adjustment, adjustable seat and an ergonomic steering wheel make these tractors simple and comfortable to operate. Some models feature hydrostatic transmissions for smooth, variable forward and reverse speed. Air Induction mowing technology improves airflow within the deck, ensuring a clean, consistent cut every time. For added versatility, all models can be equipped with a range of towable accessories and mulch kit for effective lawn fertilization.

Product may differ from image.



### **KOHLER® COURAGE ENGINE**

Fully pressure-lubricated, single-cylinder KOHLER® Courage engine with oil pump and oil filter. Powerful and quiet.



### **STEP-THROUGH**

Ensures comfortable and easy mounting and dismounting.



### **FENDER-MOUNTED CUTTING HEIGHT ADJUSTMENT**

Convenient fender mounted deck lever is spring assisted for easy operation.



### **ADJUSTABLE SLIDING SEAT**

Unique seat platform automatically changes height as seat is moved forward or rearward to optimize operator position.

## Features

- Manual blade engagement
- Cast front axle for superior stability
- Air Induction; excellent cutting performance
- Anti-scalp wheels
- Deck Wash Port
- Hour meter with service minder
- Cup holder for refreshments while mowing
- BioClip® kit/cover available as accessory
- Collector available as accessory

## Technical data

|                                  |                                                               |
|----------------------------------|---------------------------------------------------------------|
| Engine manufacturer              | Kohler                                                        |
| Engine name                      | Courage                                                       |
| Power                            | 19hp                                                          |
| Cylinder displacement            | 36.43 cu.inch / 597 cm <sup>3</sup>                           |
| Cylinders                        | 1                                                             |
| Engine cooling                   | Air                                                           |
| Generator                        | 12 A                                                          |
| Battery                          | 12 V 28 Ah                                                    |
| Fuel Type                        | Gasoline                                                      |
| Fuel tank volume                 | 1.5 gal. / 5.68 lit                                           |
| Fuel tank location               | Front                                                         |
| Engine lubrication type          | Pressure with Oilfilter                                       |
| Oil filter                       | Yes                                                           |
| Transmission type                | Fast CVT                                                      |
| Transmission manufacturer        | General Transmission                                          |
| Drive method                     | Pedal-operated                                                |
| Cutting width                    | 42 inch / 106.7 cm                                            |
| Cutting deck type                | Stamped, Reinforced                                           |
| Cutting deck material            | Steel                                                         |
| Cutting methods                  | Side discharge                                                |
| Cutting height, min-max          | 1.5 - 4 inch / 38.1 - 101.6 mm                                |
| Cutting height adjustment        | Notch                                                         |
| Cutting height steps             | 6                                                             |
| Cutting height adjuster          | Fender-mounted                                                |
| Blade engagement                 | Manual                                                        |
| Blades                           | 2                                                             |
| Blade type                       | Hi Performance                                                |
| Anti-scalp wheels                | 2                                                             |
| Nose roller                      | No                                                            |
| Powder-coated cutting deck       | Yes                                                           |
| Belt tension release             | No                                                            |
| Greasable mandrels               | No                                                            |
| Deck Wash Port                   | Yes                                                           |
| Seat back height                 | Medium                                                        |
| Seat material                    | Vinyl                                                         |
| Steering wheel type              | Standard                                                      |
| Front-End Protection             | Optional                                                      |
| Hour meter                       | Digital with pre-programmed service intervals                 |
| Collector                        | Available as accessory                                        |
| BioClip® kit/plate               | Available as accessory                                        |
| Tyre size, front                 | 15x6-6"                                                       |
| Tyre size, rear                  | 20x8-8"                                                       |
| Turning radius, min              | 16" / 40.6 cm                                                 |
| Base machine, length             | 69.3 inch / 176 cm                                            |
| Base machine, width              | 48 inch / 121.9 cm                                            |
| Base machine, width (chute down) | 49 inch / 124.5 cm                                            |
| Base machine, width (chute up)   | 44 inch / 111.7 cm                                            |
| Base machine, height             | 41.4 inch / 105.1 cm                                          |
| Weight                           | 436 lbs / 197.8 kg                                            |
| Homeowner Warranty               | 3 Year Limited / 5 Year Chassis and Axle / 10 Year Deck Shell |

### ARTICLES

960 48 00-68 Canada

