




YTA1946

Husqvarna tractors offer premium performance with quality results. Their compact size makes them easy to manoeuvre and require less space for storage. Features such as fender-mounted cutting height adjustment, adjustable seat and an ergonomic steering wheel make these tractors simple and comfortable to operate. Some models feature hydrostatic transmissions for smooth, variable forward and reverse speed. Air Induction mowing technology improves airflow within the deck, ensuring a clean, consistent cut every time. For added versatility, all models can be equipped with a range of towable accessories and mulch kit for effective lawn fertilization.

Product may differ from image.



ELECTRIC ENGAGEMENT OF CUTTING BLADE/S

Easy engagement of cutting blade/s; simply pull the switch on the control panel.



STEP-THROUGH

Ensures comfortable and easy mounting and dismounting.



FENDER-MOUNTED CUTTING HEIGHT ADJUSTMENT

Convenient fender mounted deck lever is spring assisted for easy operation.



ADJUSTABLE SLIDING SEAT

Unique seat platform automatically changes height as seat is moved forward or rearward to optimize operator position.

Features

- Cast front axle for superiour stability
- Air Induction; excellent cutting performance
- Anti-scalp wheels
- Deck Wash Port
- Fuel level window
- Hour meter with service minder
- Cup holder for refreshments while mowing
- Headlights for operation in dark conditions
- Collector available as accessory

Technical data

Engine manufacturer	Briggs & Stratton
Engine name	Endurance Series
Power	19 hp
Cylinder displacement	32.95 cu.inch / 540 cm ³
Cylinders	1
Engine cooling	Air
Generator	5&3 A
Battery	12 V 28 Ah
Fuel Type	Gasoline
Fuel tank volume	2.5 gal. / 9.46 lit
Fuel tank location	Front
Engine lubrication type	Pressure with Oilfilter
Oil filter	Yes
Transmission type	CVT
Transmission manufacturer	General Transmission
Drive method	Pedal-operated
Speed forward, min-max	0-5.2 mph / 0-8.4 km/h
Speed reverse, min-max	0-2.9 mph / 0-4.7 km/h
Cutting width	46 inch / 116.8 cm
Cutting deck type	Stamped, Reinforced
Cutting deck material	Steel
Cutting methods	Side discharge
Cutting height, min-max	1.5 - 4 inch / 38.1 - 101.6 mm
Cutting height adjustment	Notch
Cutting height steps	6
Cutting height adjuster	Fender-mounted
Blade engagement	Electric
Blades	2
Blade type	Hi Performance
Anti-scalp wheels	2
Nose roller	No
Powder-coated cutting deck	Yes
Belt tension release	No
Greasable mandrels	No
Deck Wash Port	Yes
Seat back height	High
Seat material	Vinyl
Steering wheel type	Deluxe Overmolded
Front-End Protection	Tube Bumper
Hour meter	Digital with pre-programmed service intervals
Collector	Available as accessory
BioClip® kit/plate	Available as accessory
Tyre size, front	15x6-6"
Tyre size, rear	20x8-8"
Turning radius, min	16" / 40.6 cm
Base machine, length	69.3 inch / 176 cm
Base machine, width	48 inch / 121.9 cm
Base machine, width (chute down)	56.7 inch / 144 cm
Base machine, width (chute up)	48 inch / 121.9 cm
Base machine, height	41.4 inch / 105.1 cm
Weight	443 lbs / 200.94 kg
Homeowner Warranty	3 Year Limited / 5 Year Chassis and Axle / 10 Year Deck Shell

ARTICLES

960 48 00-55 Canada

