



YTH24K48

Husqvarna tractors offer premium performance with quality results. Their compact size makes them easy to manoeuvre and require less space for storage. Features such as fender-mounted cutting height adjustment, adjustable seat and an ergonomic steering wheel make these tractors simple and comfortable to operate. Some models feature hydrostatic transmissions for smooth, variable forward and reverse speed. Air Induction mowing technology improves airflow within the deck, ensuring a clean, consistent cut every time. For added versatility, all models can be equipped with a range of towable accessories and mulch kit for effective lawn fertilization.

Product shown with optional arm rests.



PEDAL-OPERATED HYDROSTATIC TRANSMISSION

Speed and direction are managed by pedals, which lets you keep both hands on the steering wheel, for optimum driving control.



CRUISE CONTROL

Allows the tractor to maintain consistent speed, even in rough terrain.



ELECTRIC ENGAGEMENT OF CUTTING BLADE/S

Easy engagement of cutting blade/s; simply pull the switch on the control panel.



STEP-THROUGH

Ensures comfortable and easy mounting and dismounting.

Features

- Easy-access cutting height adjustment
- Adjustable seat, while seated
- Ergonomic steering wheel
- Cast front axle for superior stability
- Reinforced Deck
- Air Induction; excellent cutting performance
- Anti-scalp wheels
- Deck Wash Port
- Cup holder for refreshments while mowing
- Collector available as accessory

Technical data

Engine manufacturer	Kohler
Engine name	KT 7000
Power	24 hp
Cylinder displacement	44.2 cu.inch / 725 cm ³
Cylinders	2
Engine cooling	Air
Generator	12 A
Battery	12 V 28 Ah
Fuel Type	Gasoline
Fuel tank volume	2.5 gal. / 9.46 lit
Fuel tank location	Front
Engine lubrication type	Pressure with Oilfilter
Oil filter	Yes
Transmission type	Hydrostatic
Transmission manufacturer	Tuff Torq
Drive method	Pedal-operated
Speed forward, min-max	0-5.2 mph / 0-8.4 km/h
Speed reverse, min-max	0-2.9 mph / 0-4.7 km/h
Cutting width	48 inch / 121.9 cm
Cutting deck type	Stamped, Reinforced
Cutting deck material	Steel
Cutting methods	Side discharge
Cutting height, min-max	1.5 - 4 inch / 38.1 - 101.6 mm
Cutting height adjustment	Notch
Cutting height steps	6
Cutting height adjuster	Fender-mounted
Blade engagement	Electric clutch
Blades	3
Blade type	Hi Performance
Anti-scalp wheels	4
Nose roller	No
Powder-coated cutting deck	Yes
Belt tension release	Yes
Greasable mandrels	Yes
Deck Wash Port	Yes
Seat back height	High
Seat material	Vinyl
Steering wheel type	Deluxe Overmolded
Front-End Protection	Optional
Hour meter	Yes
Collector	Available as accessory
BioClip® kit/plate	Available as accessory
Tyre size, front	15x6-6"
Tyre size, rear	20x8-8"
Turning radius, min	16" / 40.6 cm
Wheelbase	48" / 121.9 cm
Base machine, length	69.3 inch / 175.9 cm
Base machine, width (chute down)	59.8 inch / 151.8 cm
Base machine, width (chute up)	50.8 inch / 128.9 cm
Base machine, height	41.4 inch / 105.1 cm
Weight	477 lbs / 216.37 kg
Homeowner Warranty	3 Year Limited / 5 Year Chassis and Axle / 10 Year Deck Shell

ARTICLES

960 48 00-60 Canada

