



YT48XLS

We developed our LS series yard tractors with the discriminating landowner in mind. Engineered for added durability, comfort, style and precision, our LS series yard tractors all feature fabricated or reinforced cutting decks, heavy-duty chassis and cast iron axles. Optional grass baggers, mulch kits and a host of other attachments make these models ideal for demanding and extensive use in various applications. Automatic locking rear differential increases traction while cutting wet grass or on slopes.



KOHLER® V-TWIN ENGINE

Fully pressure-lubricated, two-cylinder KOHLER® engine with oil pump and oil filter. Powerful and quiet.



HYDROSTATIC TRANSMISSION WITH LOCKING DIFFERENTIAL

The pedal operated hydrostatic transmission offers a smooth, variable forward and reverse speed while the standard automatic locking rear differential increases traction while cutting on slopes or wet grass.



CRUISE CONTROL

Allows the tractor to maintain consistent speed, even in rough terrain.



ELECTRIC ENGAGEMENT OF CUTTING BLADE/S

Easy engagement of cutting blade/s; simply pull the switch on the control panel.

Features

- Step-through for easy mounting
- Easy-access cutting height adjustment
- Adjustable seat, while seated
- Ergonomic steering wheel
- Battery indicator with charger connection
- Cast front axle for superior stability
- Durable cutting deck
- Anti-scalp wheels
- Deck Wash Port
- Fuel level window
- Hour meter with service minder
- Cup holder for refreshments while mowing
- Headlights for operation in dark conditions
- Brushguard for protection of the hood
- Collector available as accessory

Technical data

Engine manufacturer	Kohler
Power	26 hp
Cylinder displacement	45.58 cu.inch / 747 cm³
Cylinders	2
Engine cooling	Air
Generator	15 A
Battery	12 V 28 Ah
Fuel Type	Gasoline
Fuel tank volume	4 gal. / 15.1 lit
Fuel tank location	Rear
Engine lubrication type	Full pressure
Oil filter	Yes
Transmission type	Hydrostatic
Transmission manufacturer	Tuff Torq
Drive method	Pedal-operated
Speed forward, min-max	0-5.5 mph / 0-8.8 km/h
Speed reverse, min-max	0-2.4 mph / 0-3.9 km/h
Cutting width	48 inch / 121.9 cm
Cutting deck type	Fabricated
Cutting deck material	Steel
Cutting methods	Collect/Mulch/Side ejection
Cutting height, min-max	1.5 - 4 inch / 38.1 - 101.6 mm
Cutting height adjustment	Notch
Cutting height steps	7
Cutting height adjuster	Fender-mounted
Blade engagement	Electric clutch
Blades	3
Blade type	HI Performance
Anti-scalp wheels	4
Nose roller	Yes
Powder-coated cutting deck	Yes
Greasable mandrels	Yes
Deck Wash Port	Yes
Seat back height	High
Seat material	Vinyl
Steering wheel type	Deluxe Overmolded
Front-End Protection	Brush Guard Style Bumper
Hour meter	Yes
Aluminum Racing Foot Pedal	Yes
Collector	Available as accessory
BioClip® kit/plate	Available as accessory
Tyre size, front	16x6.5-8"
Tyre size, rear	20x10-8"
Turning radius, min	16" / 40.64 cm
Wheelbase	48" / 121.9 cm
Base machine, length	69.25 inch / 175.9 cm
Base machine, width (chute down)	62.3 inch / 158.2 cm
Base machine, width (chute up)	48.7 inch / 123.7 cm
Base machine, height	41.4 inch / 105.2 cm
Weight	596 lbs / 270.3 kg
Homeowner Warranty	3 Year Limited / 5 Year Chassis and Axle / Lifetime Limited Deck Shell

ARTICLES

960 48 00-85 Canada

