



AR 19

Professional aerator for reliable and long-term use. Ventilates compact lawn surfaces by punching out cylindrical plugs of earth. Rugged, all-welded steel construction with removable weights.

The 5 tines wide unit can handle extremely tight turns, thanks to the patented free wheel design. Capacity of up to 2300 m²/hour.



COMPACT DESIGN

The compact design, foldable handle, detachable weights and lifting handle facilitate loading and transport.



FREE-WHEEL DESIGN

The unique patented free-wheel design of the 48 cm, 5-tine wide cutting deck provides optimal manoeuvrability. Allows tight turns while working at a capacity of up to 2,300 m² per hour.



DETACHABLE WEIGHTS

Detachable weights for efficient, stable operation where the ground conditions require, such as on slopes.



REAR-WHEEL CONTROL

Rear-wheel control, allowing adjustment of working depth and settings for maximal stability.

Features

- Robust design for demanding use
- Sealed bearings provide reliability
- Powerful and easy to start Honda engine
- Commercial components ensure years of use

Technical data

Engine manufacturer	Honda
Engine name	GX Series
Net power at preset rpm	2.6 kW @ 3600 rpm
Cylinder displacement	7.3 cu.inch / 119 cm ³
Engine lubrication type	Splash
Fuel tank volume	0.53 gal. / 2 lit
Transmission type	V belt to jackshaft
Aerating pattern	3.8x6.5 inch / 97x165 mm
Working depth	3" / 7.6 cm
Aerating width	19 inch / 48 cm
Working depth adjustment	Knob
Number of tines	30
Free-wheel design	Yes
Detachable weights	2x16.3
Foldable handlebar	Yes
Tyre size, front	10x6 inch
Tyre size, rear	8x2 inch
Base machine, length	57.5 inch / 146 cm
Base machine, width	29.9 inch / 76 cm
Base machine, height	51.6 inch / 131 cm
Product size, LxWxH, folded handle	39.6x29.9x37 inch / 100.5x76x94 cm
Weight	291 lbs / 131 kg
Frame Construction	Steel

ARTICLES

968 98 21-02 AR 19

