



338 XP® T

338 XP® T represent a new upgraded edition with increased compression ratio for more rapid acceleration and increased torque. The new Husqvarna 338 XP® T is the result of the successful further development of the previous model. Higher performance and longer operating times ensure maximum efficiency, and the soft inlays on the handle, a new choke/stop control and chain tensioning from the side are other improvements aimed at easier operation and better working environment. XP®



CHAIN TENSIONING FROM THE SIDE

Allows quick and convenient chain tensioning.



SOFT INLAYS

Provide a firm, comfortable grip that reduces fatigue and makes the saw easier to handle.



HAND GUARD

The design of the hand guard allows easier view of the tip of the saw bar, and improved control when operating.



ROPE ATTACHMENT

A sturdy point for fastening a rope, making it easy to hoist the saw up into a tree.

Features

- Easy to manoeuvre with teardrop- shape design
- Less filter cleanings with Air Injection
- LowVib® sparing the user's arms and hands
- Maximum durability for tough applications
- Adjustable chain oil pump
- Intuitive, combined choke/stop control
- Magnesium crankcase designed for professional use
- Easy to maintain with snap locked filter cover
- Smart Start® for easy starting
- Fuel pump for easy starting
- Increased safety, inertia activated chain brake

Technical data

Cylinder displacement	2.4 cu.inch / 39 cm ³
Power output	2.3 hp / 1.7 kW
Maximum power speed	9600 rpm
Fuel tank volume	11.5 fl oz / 0.34 lit
Fuel consumption	540 g/kWh
Idling speed	2800 rpm
Spark plug	Champion RCJ7Y, NGK BPMR7A
Electrode gap	0.02" / 0.5 mm
Torque, max.	1.8 Nm / 7200 rpm
Oil tank volume	0.3 US pint / 0.14 lit
Oil pump type	Automatic
Equivalent vibration level (ahv, eq) front / rear handle	3/3.5 m/s ²
Sound pressure level at operators ear	102 dB(A)
Sound power level, guaranteed (LWA)	111 dB(A)
Chain pitch	3/8"
Recommended bar length, min-max	12"-16" / 30-40 cm
Chain speed at max power	60.04 fts / 18.3 m/s
Chain speed at 133% of maximum engine power speed	79.72 fts / 24.3 m/s
Chain gauge	0.05 "
Weight (excl. cutting equipment)	7.7 lbs / 3.5 kg

ARTICLES

965 25 11-14 14" - 3/8 - S36 - EPA, AS, US, CA

