



543 XP®

When professionals need to do serious work, one chainsaw feature becomes more important than any other: weight. Ready for any professional grade task the new Husqvarna 543 XP® can be used for hours at a time, without the burden of heavy equipment. Outfitted with X-Torq™ the 543 XP® has 20 per cent less fuel consumption and up to 75 per cent less emission. Couple this with Husqvarna's Smart Start® technology, which reduces pull cord resistance allowing for a quick start, the 543 XP® is designed to save time and money, making it the ideal companion on any job site.



MAGNESIUM CRANKCASE

Sturdily built crankcase withstands high rpms and tough professional use, ensuring a long service life.



X-TORQ®

Deliver lower fuel consumption and reduced exhaust emission levels in accordance with the world's most stringent environmental regulations.



ADJUSTABLE OIL PUMP

Adjustable oil pump makes it easy to set the chain lubrication according to your needs.



AIR INJECTION

Centrifugal air cleaning system for reduced wear and longer operating time between filter cleanings.

Features

- LowVib® sparing the user's arms and hands
- Auto return stop switch for easy starting
- Quick and easy chain adjustment
- Fuel pump for easy starting
- Maximum durability for tough applications
- Smart Start® for easy starting
- Felling marks for correct felling direction
- Increased safety, inertia activated chain brake

Technical data

Cylinder displacement	2.63 cu.inch / 43.1 cm ³
Power output	2.95 hp / 2.2 kW
Maximum power speed	9600 rpm
Fuel tank volume	14.2 fl oz / 0.42 lit
Fuel consumption	467 g/kWh
Idling speed	2700 rpm
Spark plug	NGK CMR7H
Electrode gap	0.03 " / 0.65 mm
Torque, max.	2.4 Nm / 7200 rpm
Oil tank volume	0.57 US pint / 0.27 lit
Oil pump type	Adjustable flow, no flow at idle
Equivalent vibration level (ahv, eq) front / rear handle	2.8/3.5 m/s ²
Sound pressure level at operators ear	101 dB(A)
Sound power level, guaranteed (LWA)	113 dB(A)
Chain pitch	.325"
Recommended bar length, min-max	13"-18" / 33-45 cm
Chain speed at max power	66.27 fts / 20.2 m/s
Chain gauge	0.05 "
Weight (excl. cutting equipment)	9.92 lbs / 4.5 kg

ARTICLES

967 14 62-02 16" - .325" H30 (NA)

