





T540 XP®

Husqvarna T540 XP® is designed for the high-end top handle saw segment, targeting professional customers like full pro arborists, landscapers, garden contractors and utility services who need excellent performance in combination with the best ergonomics.



AUTOTUNE

AutoTune gives optimal engine performance throughout automatic engine setting. No time spent on carburettor adjustments. It compensates for different fuels, altitude, humidity, temperature and clogged air filter.



X-TORQ®

Deliver lower fuel consumption and reduced exhaust emission levels in accordance with the world's most stringent environmental regulations.



INDIVIDUAL GRIP SIZE

The top handle grip size can be set in three alternative sizes, to perfectly fit your hand.



BELT EYE LET

Makes it quick and easy to connect the saw to the climbing harness.

Features

- The light and strong TechLite  bar makes the saw easier to manouvre.
- Auto return stop switch for easy starting
- Less filter cleanings with Air Injection
- LowVib® sparing the user's arms and hands
- Quick-release air filter
- Adjustable chain oil pump
- Quick and easy chain adjustment
- Magnesium crankcase designed for professional use
- Easy to maintain with snap locked filter cover
- Good visibility hand guard
- Fuel level window
- Fuel pump for easy starting
- Increased safety, inertia activated chain brake

Technical data

Cylinder displacement	2.3 cu.inch / 37.7 cm ³
Power output	2.4 hp / 1.8 kW
Maximum power speed	10200 rpm
Fuel tank volume	11.5 fl oz / 0.34 lit
Fuel consumption	464 g/kWh
Idling speed	3000 rpm
Spark plug	NGK CMR6H
Electrode gap	0.02" / 0.5 mm
Torque, max.	1.79 Nm/9000 rpm
Oil tank volume	0.42 US pint / 0.2 lit
Oil pump type	Adjustable flow
Equivalent vibration level (ahv, eq) front / rear handle	3.1/3.2 m/s ²
Sound pressure level at operators ear	104 dB(A)
Sound power level, guaranteed (LWA)	116 dB(A)
Chain pitch	3/8"
Recommended bar length, min-max	12"-16" / 30-40 cm
Chain speed at max power	63.65 fts / 19.4 m/s
Chain speed at 133% of maximum engine power speed	84.65 fts / 25.8 m/s
Chain gauge	0.05"
Weight (excl. cutting equipment)	8.6 lbs / 3.9 kg

ARTICLES

966 61 10-01	Engine - EPA - US, CAN
966 61 10-14	14" , US, CAN
966 61 10-16	16" , US, CAN

