



327P5x

Pole saw with rapid acceleration and easy starting E-TECH® II engine. The versatile cutter head makes it easy to reach even dense trees and bushes without using a ladder or cherry picker. Low weight, good balance and rear-mounted engine provide a comfortable working position and reduced exhaust fumes. The cutter head has adjustable and automatic chain lubrication.




CHAIN LUBRICATION
Adjustable, automatic chain lubrication.



DETACHABLE SHAFT
Detachable shaft for easy transport and storage.



REAR IMPACT GUARD
The rear-impact guard protects the engine from wear and damage.



AUTO RETURN STOP SWITCH
Stop switch automatically resets to the ON position for trouble-free starting.

Features

- Smart Start® for easy starting
- Comfortable soft grip handles
- Inertia balancing wheel reduces vibration
- Fuel pump for easy starting
- E-TECH® II for reduced exhaust emissions

Technical data

Cylinder displacement	1.5 cu.inch / 24.5 cm ³
Power output	1.21 hp / 0.9 kW
Maximum power speed	8400 rpm
Fuel tank volume	16.91 fl oz / 0.5 lit
Fuel consumption	600 g/kWh
Idling speed	2700 rpm
Spark plug	Champion RCJ6Y
Electrode gap	0.02" / 0.5 mm
Oil tank volume	0.5 US pint / 0.22 lit
Equivalent vibration level (ahv, eq) front / rear handle	3.4/1.9 m/s ²
Sound pressure level at operators ear	86 dB(A)
Sound power level, guaranteed (LWA)	105 dB(A)
Chain pitch	3/8"
Recommended bar length, min-max	10"-12" / 25-30 cm
Weight (excl. cutting equipment)	14.11 lbs / 6.4 kg
Length, extended, including cutting equipment	137.8" / 350 cm

ARTICLES

966 97 67-01 US50 ex Lowes

