



## 327LDx

The Husqvarna 327LDx is a lightweight, high performance trimmer. The machine is equipped with Husqvarna's E-TECH® II engine with catalytic emission control, soft and comfortable handles. The 327LDx is a combination machine, developed for many different types of job. Power head only. Several attachments are available as accessories.



### DETACHABLE SHAFT

Detachable shaft for easy transport and storage.




### CLICK ON ATTACHMENTS

Click on attachments for easy tool change.



### SMART START®

The engine and starter have been designed so the machine starts quickly with minimum effort. Resistance in the starter cord is reduced by up to 40%.



### AUTO RETURN STOP SWITCH

Stop switch automatically resets to the ON position for trouble-free starting.

## Features

- Comfortable handle design
- Soft grip handles
- Comfortable handles
- Fuel pump for easy starting
- E-TECH® II for reduced exhaust emissions

## Technical data

|                                                          |                                      |
|----------------------------------------------------------|--------------------------------------|
| Cylinder displacement                                    | 1.5 cu.inch / 24.5 cm <sup>3</sup>   |
| Power output                                             | 1.2 hp / 0.9 kW                      |
| Maximum power speed                                      | 8400 rpm                             |
| Fuel tank volume                                         | 16.9 fl oz / 0.5 lit                 |
| Fuel consumption                                         | 600 g/kWh                            |
| Fuel consumption                                         | 1.21 lbs/h / 0.55 kg/h               |
| Idling speed                                             | 2700 rpm                             |
| Spark plug                                               | Champion RCJ6Y                       |
| Electrode gap                                            | 0.02" / 0.5 mm                       |
| Clutch engagement speed                                  | 3950 rpm (± 120 rpm)                 |
| Lubricant type                                           | Husqvarna 2 stroke or equiv. at 50:1 |
| Maximum rpm output shaft                                 | 8300 rpm                             |
| Output shaft thread                                      | M10x1.25V                            |
| Lubricant type (bevel gear)                              | Mineral grease                       |
| Exhaust emissions (CO average)                           | 153 g/kWh                            |
| Equivalent vibration level (ahv, eq) left / right handle | 2.9/3.4 m/s <sup>2</sup>             |
| Sound pressure level at operators ear                    | 94 dB(A)                             |
| Sound power level, guaranteed (LWA)                      | 110 dB(A)                            |
| Gear ratio                                               | 1:1.46                               |
| Drive gear angle                                         | 30 °                                 |
| OEM Trimmer head                                         | T35 M10                              |
| Weight (excl. cutting equipment)                         | 11.24 lbs / 5.1 kg                   |
| Tube length                                              | 58.39 inch / 1483 mm                 |
| Tube diameter                                            | 0.94" / 24 mm                        |

### ARTICLES

|              |                         |
|--------------|-------------------------|
| 966 97 69-01 | T35, CAN, US50 ex Lowes |
|--------------|-------------------------|

