

With a selection of available transmission options, these versatile, compact 4WD tractors easily handle medium to heavy-duty applications.



Joystick Lever



Telescopic lower link

- 4-cylinder diesel engine
- 12 x 12 synchro-shuttle or 3-range HST transmission
- Push-button-operated independent PTO
- Telescopic lower link
- Two sets of remote-control valves
- Available with quick-attach skid-steer-compatible front-end loader
- Loader control joystick lever
- Optional mid-mount PTO
- Your choice of Industrial, Ag or Turf tires
- 5-year warranty



*5-year limited warranty. See dealer for details.

Pursue your passion



R-Series

R3039

R3039H

ENGINE	
Type	4 - Cylinder, Indirect - injection, Water - cooled
Model (Tier 3)	Mitsubishi S4L2
Engine HP (Gross)	38.5
PTO HP	31 29
Rated speed, RPM	2700
Displacement-cu, In.	107.3
Fuel tank capacity (gal)	8.4
Alternator	12V - 50 Amps
DRIVE TRAIN	
Transmission	Synchro shuttle Hydrostatic Drive
No. of Speeds	12F / 12 R 3 Ranges
Brakes	Wet, Multi - disc
Steering	Hydrostatic Power Steering
PTO	
Type	Independent or Manual Independent
Rear(rpm)	Standard (540 rpm)
Mid PTO	Field Option (2000 rpm)
HYDRAULIC SYSTEM	
Implement pump, gpm	8.6
Steering pump, gpm	4.3
Total flow, gpm	12.9
Category, 3pt hitch	CAT 1
Hitch Lift capacity, lbs	1808
Lift control type	Position / Draft
DIMENSIONS	
Overall length with 3pt, in.	117.6
Min. overall width with Ag tires, in.	54.3
Wheelbase, in.	65.4
Ht to top of rops. with Ag tires, in.	92.6
TIRE SIZE	
Ag Front / Rear	7 - 14 / 11.2 - 24
IND Front / Rear	25 x 8.5 - 14 / 43 x 16 - 20
Turf Front / Rear	25 x 8.5 - 14 / 41 x 14 - 20
WEIGHT	
Total weight without ballast, lbs	2780

Note Specifications and design are subject to change without prior notice.

Implement

Front end Loader

LL3103

Tractor Application	R3039 / R3039H
Maximum Lift Height, in.	91.7
Clearance with Attachment Dump, in.	60.7
Reach at Maximum Height, in.	20.2
Maximum Dump Angle, deg.	48
Maximum Rollback Angle, deg.	38
Digging Depth, in.	5.9
Overall Height in Carry Position, in.	43
Lift Capacity (@ Pivot Pin), lbs.	2250
Breakout Force (@ Pivot pin), lbs.	2746
Approx. Weight (Loader w/o Bucket), lbs.	1058

Backhoe

LB2100

Tractor Application	R3039 / R3039H
Digging Depth, in	89.7
Reach From centerline of swing Pivot, in.	125.1
Loading Height, in.	72.4
Swing Arc, deg.	180
Transport Height, in.	83.5
Bucket Rotation, deg.	180
Stabilizer Spread (Down Position), in.	68.7
Stabilizer Spread (Up Position), in.	46.4
Bucket Digging force, lbs.	2679

Mid-Mount Mower

LM3566

Tractor Application	R3039 / R3039H
Cutting Width, in.	66
Overall Width, in.	81
Cutting Height Range, in.	1 to 4
Deck shell Thickness, in.	10-Gauge (0.1345 in.) Grade 50 steel
Spindle Speed at 2800 RPM	3056 RPM
Blade Tip Speed ft./min	18,200
Number of Blades	3
Blade Length, in.	25
Blade Width, in.	2-1/2
Blade Thickness, in.	1/4
Shipping Weight of Base 66" Deck, lbs.	540

Standard Equipment

- Dry-type air cleaner
- Pre-heat starting aid
- Hand and foot accelerator control
- Instrumentation-alternator
- Warning and engine oil pressure light
- Remote-control valve (2 pairs)
- Hydrostatic power steering
- Front loader valve and loader joystick
- Hydraulic draft and position control
- Rear working light
- Adjustable seat
- Telescopic stabilizer & Drawbar
- ROPS w/seat belt
- Safety flashers
- Turn signals

LS Tractor USA

Dealer Imprint Zone