


Versatility in a large-horsepower, compact-size 4WD is combined with features designed to take on heavy-duty jobs with ease.



Joystick Lever



Telescopic lower link

- 16 x 16 synchro-shuttle or 3-range HST transmission
- 16 x 16 EZ Shift (Automated Mechanical transmission)
- Push-button-operated independent PTO
- Telescopic lower link
- Two sets of remote-control valves
- Available with quick-attach skid-steer-compatible front-end loader
- Loader control joystick lever
- Optional mid-mount PTO
- Your choice of Industrial, Ag or Turf tires
- 5-year warranty



*5-year limited warranty. See dealer for details.

Pursue your passion



R-Series

R4041

R4041 EZ

R4041H

ENGINE			
Type	4 - Cylinder, Indirect - injection, Water - cooled		
Model (Tier 3)	LS - Mitsubishi S4QL - D		
Engine HP (Gross)	41		
PTO HP	35		33
Rated speed, RPM	2600		
Displacement-cu, In.	152.9		
Fuel tank capacity (gal)	9.5		
Alternator	12V - 50 Amps		
DRIVE TRAIN			
Transmission	Synchro shuttle	EZ shift	Hydrostatic Drive
No. of Speeds	16F / 16 R		3 Ranges
Brakes	Wet, Multi - disc		
Steering	Hydrostatic Power Steering		
PTO			
Type	Fully Independent or Manual		Independent
Rear(rpm)	Standard (540 rpm)		
Mid PTO	Field Option (2000 rpm)		
HYDRAULIC SYSTEM			
Implement pump, gpm	8.2		
Steering pump, gpm	4.1		5.5
Total flow, gpm	12.3		13.7
Category, 3pt hitch	CAT 1		
Hitch Lift capacity, lbs	2755		
Lift control type	Position / Draft		
DIMENSIONS			
Overall length with 3pt, in.	132.2		
Min. overall width with Ag tires, in.	55.9		
Wheelbase, in.	69.2		
Ht to top of rops. with Ag tires, in.	95.1		
TIRE SIZE			
Ag Front / Rear	9.5 - 16 / 12.4 - 24		
IND Front / Rear	10 x 16.5 / 43 x 16 - 20		
Turf Front / Rear	28 x 8.5 - 15 / 41 x 14 - 20		
WEIGHT			
Total weight without ballast, lbs	3813		

Note Specifications and design are subject to change without prior notice.

Implement

Front end Loader

LL4101

Tractor Application	R-SERIES
Maximum Lift Height, in.	96.1
Clearance with Attachment Dump, in.	65.8
Reach at Maximum Height, in.	24.5
Maximum Dump Angle, deg.	47
Maximum Rollback Angle, deg.	34
Digging Depth, in.	5.9
Overall Height in Carry Position, in.	50.4
Lift Capacity (@ Pivot Pin), lbs.	2500
Breakout Force (@ Pivot pin), lbs.	4354
Approx. Weight (Loader w/o Bucket), lbs.	1102

Backhoe

LB2101

Tractor Application	R-SERIES
Digging Depth, in	89.7
Reach From centerline of swing Pivot, in.	125.1
Loading Height, in.	72.4
Swing Arc, deg.	180
Transport Height, in.	83.5
Bucket Rotation, deg.	180
Stabilizer Spread (Down Position), in.	68.7
Stabilizer Spread (Up Position), in.	46.4
Bucket Digging force, lbs.	2679

Standard Equipment

- Dry-type air cleaner
- Pre-heat starting aid
- Hand and foot throttle control
- Instrumentation-alternator
- Warning and engine oil pressure light
- Remote-control valve (2 pairs)
- Hydrostatic power steering
- Front loader valve and loader joystick
- Hydraulic draft and position control
- Rear working light
- Adjustable seat
- Telescopic stabilizer & Drawbar
- ROPS w/seat belt
- Safety flashers
- Turn signals

LS Tractor USA

Dealer Imprint Zone