

WALKER MOWERS

out front mowing

Model MD Diesel

**3-Year
Warranty**
on Drive System*

*Pro-rated based on 3,000 hours

Powered By

Kubota

Model MD

A top-of-the-line Kubota diesel engine, the Model MD provides long life and fuel economy, and forms the core of the Model MD, a hard working, proven performer for commercial lawn mowers.

- 20.9-hp Kubota liquid-cooled, three-cylinder diesel engine
- Electric radiator fan with reversible self-cleaning action
- Clam-shell style body and chassis to accommodate higher horsepower engine
- Shock-mounted instrument panel with warning lights and horn; also includes ignition switch, light switch (opt), water temp gauge, voltmeter, and hourmeter
- 10.0 bushel catcher (7.0 bu. option) and 10.5" blower on GHS Models
- Grammer suspension seat w/ armrests
- Dual tail wheels for extra flotation
- 4.7-gallon fuel tank
- Remote air intake for engine
- Splined PTO drive shaft with quick-disconnect coupler
- High capacity electrical system (40-amp charge)
- 7 mph ground speed



Key Engine Specifications

• Manufacturer/Model	Kubota, D722, 3 cyl.
• Displacement	722 cc (44 cu. in.)
• Horsepower/RPM	20.9 @ 3600
• Max Torque (ft-lbs)	34 @ 2600
• Fuel	Diesel Fuel (2-D)
• Fuel Capacity (U.S. gal)	4.7 (17.8 liter)
• Fuel Consumption (per hour)	.76 gallon (2.88 liter)
• Cooling System	Liquid, Radiator
• Lubrication System	Full Pressure w/ Filter

Quick Reference Dimensions

Tractor	Weight*	Overall Dimensions
SD Tractor	787	
GHS Tractor	932	
SD Tractor & Deck*	980	37 H x 50 [^] W x 91 L
GHS Tractor & Deck*	1130	49 H x 49 W x 91 L

* Approximate Pounds * Dimensions and weight shown for models equipped with 48" deck (typical)

[^] 48" deck with discharge shield folded

Popular Options

- Hi-Dump®
- Low-Profile Drive Tires (10.5)
- All-Terrain Drive Tires
- No-Catch Deflector
- GHS Blower Lockout
- 7.0 Bushel Catcher
- Tail Weight
- Mechanical Deck Lift
- Power Deck Lift
- Power Dump
- Tire Chains
- Headlights
- Tail Wheel Lock

Compatible Decks

- Grass Handling (GHS) - 36", 42", 48", 52"
- Mulching (ML) - 36", 42", 48", 52"
- Side Discharge (SD) - 36", 42", 48", 52", 56", 62", 74"

Compatible Implements/Attachments

- Implement Hitch
- Operator Soft Cab
- Rotary Broom
- Loader Bucket
- Single-Stage Snowblower (36")
- Two-Stage Snowblower (42")
- Debris Blower
- Dozer Blade
- Coulter Blade Edger



walkermowers.com