



# ATV PLOWS

APPLICATIONS: ATVs



SPECIFICATIONS	4' Straight-Blade (Poly)	5' Straight-Blade (Poly)
Blade Width (Straight)	48" (121.92 cm)	60" (152.40 cm)
Plowing Width @ 30° Angle	N/A	52" (132.08 cm)
Blade Height	22" (55.88 cm)	22" (55.88 cm)
Blade Material	1/8" Poly (0.32 cm)	1/8" Poly (0.32 cm)
Vertical Support Ribs	4	4
Trip Return Springs	2	2
Cutting Edge	1/4" (.64 cm) x 4" (10.16 cm) Reversible	1/4" (.64 cm) x 4" (10.16 cm) Reversible
Undercarriage	Low profile (trail compatible)	Low profile (trail compatible)
Plow Lifting	Hydraulic	Hydraulic
Plow Angling	Hydraulic	Hydraulic
Hydraulic Package	High performance (comes off with the plow)	High performance (comes off with the plow)
Quick Attach System	Quick Attach	Quick Attach
Paint Finish	SmartShield	SmartShield
Controller	Switch Box	Switch Box
Weight Complete	170 lb (77 kg)	190 lb (86 kg)
Tripping Mechanism	Full-blade trip design	Full-blade trip design
Warranty	2-year limited warranty	2-year limited warranty
Snow Deflector	Optional	Optional

**TWO-YEAR LIMITED WARRANTY** - All BOSS Snowplows and equipment are guaranteed to be free from defects in material and workmanship for two full years from the date of purchase. Stop by any Authroized BOSS dealer to receive complete details on our Two-year parts and labor warranty.

**LEGAL STATEMENT** - Vehicles intended to be equipped with a spreader and/or snowplow must comply with the vehicle manufacturers' specifications for equipment application. BOSS Products/Northern Star Industries, Inc. reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications use herein.

**BOSS Products are covered under one or more of the following patent numbers: U.S. Patents: 4,074,448; 4,658,519; 5,568,694; 6,170,178; 6,134,814; 6,108,946; 6,467,199; 7,437,839; 8,793,907; 8,978,276; 9,051,700. Canadian Patents: 1,300,877; 2,330,135. Other patents pending. ©2015 BOSS Products/The Toro Company. All rights reserved.**