

Put your harvesting on fast-forward.

MacDon



MACDON PW7 PICK-UP HEADER

PW7 PICK-UP HEADER FEATURES

- New header mounting allows the auger to be mounted closer to the feeder chain for better feeding.
- Single point hook up for hydraulics, electrical and locking pins.
- Left-hand PTO hook-up.
- PTO shafts come with radial pin clutch.
- Chain tension is adjusted by moving PTO drive, eliminating the chain tension idler.
- Replaceable floor panel.
- Ultra float suspension system carries and supports pick-up.
- Durable polyethylene side safety shield.
- Finger timing and auger chain tension can get adjusted without removing side shields.

RAKE UP™ SERIES IV FEATURES

- Built to pick more crop, especially in tough conditions.
- Built to leave stones behind.
- Hydraulically operated crop hold-down.
- Standard plastic teeth with optional steel.
- New large 20 x 10 – 10 flotation tires.
- New wheel height adjustment.
- Ultra float suspension.

SWATHMASTER™ SERIES IV FEATURES

New features and design for improved performance, reliability and operator convenience.

- Front belt rear roller middle support, now standard on the 16' model to greatly reduce belt slippage.
- Orbit motor on front belt for direct pull, with self-tightening V-belt drive of rear belt.
- New wheel height adjustment and new large 20 x 10 – 10 flotation tires along with ultra float suspension for improved stability, reduced wheel bounce and reduced ground pressure.
- Reduced number of grease points.
- Draper roller mounting position reduces grain loss and back feeding.
- Hydraulically operated crop hold-down.
- High quality plastic fingers are standard, steel teeth are optional.

MACDON LOCATIONS AROUND THE WORLD

Winnipeg, Canada | Kansas City, United States | Melbourne, Australia | Moscow, Russia

MacDon
60 years strong

PW7 PICK-UP HEADER SPECIFICATIONS

Header Size	13 ft. (4 m)	15 ft. (4.6 m)
Weight	1,550 lbs. (703 kg)	1,600 lbs. (726 kg)
Overall Width	171 in. (4 343 mm), 192 in. (4 877 mm) with clearance lights	190 in. (4 826 mm) 211 in. (5 359 mm) with clearance lights
Overall Height	45 in. (1 143 mm) with clearance lights	45 in. (1 143 mm) with clearance lights
Overall Depth	35 in. (889 mm)	35 in. (889 mm)
Header Opening Width	154 in. (3 912 mm)	173 in. (4 394 mm)
Auger Diameter	24 in. (610 mm)	24 in. (610 mm)
Auger Fingers	0.625 in. (16 mm) induction hardened, 18 - 24 fingers (depending on machine)	
Auger Speed	150 - 217 RPM (depending on combine)	
Drive Shaft	Heavy duty, fully shielded with built-in clutch	

RAKE-UP™ IV SPECIFICATIONS

Size	14 ft. (4.27 m)	16 ft. (4.88 m)
Number of 19 in. Draper Belts	8	9
Actual Picking Width	154 in. (3 912 mm)	175 in. (4 445 mm)
Mounting Bracket Width	169 in. (4 293 mm)	188 in. (4 775 mm)
Shipping Weight	1,450 lbs. (657.7 kg)	1,600 lbs. (725.7 kg)
Overall Width to Edge of Tires	204 in. (5 182 mm)	223 in. (5 664 mm)

SWATHMASTER™ IV SPECIFICATIONS

Size	14 ft. (4.27 m)	16 ft. (4.88 m)
Number of 19 in. Draper Belts	8	9
Actual Picking Width	152 in. (3 861 mm)	171 in. (4 343 mm)
Mounting Bracket Width	163 in. (4 140 mm)	182 in. (4 623 mm)
Shipping Weight	1,650 lbs. (780.4 kg)	1,700 lbs. (771.1 kg)
Overall Width to Edge of Tires	190 in. (5 826 mm)	209 in. (5 309 mm)

Prices, specifications and options subject to change without notice. Products subject to availability. Products featured may include available options.
MF12317 Printed in Canada 08/2009 Part #147550