



Quality Products Since 1968

Manufactured by:
Helm Welding (1983) Limited

Snowblowers
"Double Auger"

Standard Features



Optional Equipment

- 3 stage spout deflector
- Telescopic truck loading chute
- Reinforced end plates
- Skid shoes
- Quick hitch set-up
- Weld on cutting edge
- Reversible bolt on cutting edge
- Cylinder c/w hoses & fittings
- 1,000 rpm (not available on D7 model, standard on D9 & D10 models)

other options available upon request

See the pictures on our website for various options.

Specification Table (Double Auger Units)

MODEL SIZE	D7	D75	D8	D85	D9	D10
Weight	1195	1530	1545	1735	2130	3220
Cutting Width	84	90	96	102	108	120
Cutting Height	36	36	36	36	36	44
Fan Shaft Diameter	40 mm	1 ¾	1 ¾	2	2	2
Fan Blades	4	4	4	4	4	6
Fan Diameter	28	28	28	30	32	34
Fan Housing Width	8	12	12	12	12	12
Fan Housing (thickness)	10 ga.	3/16	3/16	3/16	3/16	3/16
Auger Diameter	17	17	17	17	17	20
Auger Shaft Diameter	1 7/16	1 7/16	1 7/16	1 7/16	1 7/16	1 3/4
Auger Flighting Thickness	½	½	½	½	½	½
Auger Chain Size	#60	#80	#80	#80	#80	#80
Chute Diameter	12	13	13	13	13	15
Chute Length	36	48	48	48	48	48
Orbital Motor Chute Rotator	Stan.	Stan.	Stan.	Stan.	Stan.	Stan.
Spout Deflector (Single)	Stan.	Stan.	Stan.	Stan.	Stan.	Stan.
Hitch Category	1 & 2	2	2	2	2	2
Rec. H.P. (min)	70	80	90	100	120	140
Rec. H.P. (max)	90	105	115	150	160	180

H.P. recommendations are suggested only (pending snow and ground speed conditions and transmission type)

Unless otherwise indicated, all dimensions are in inches with standard equipment installed.

Specifications subject to change without notice.

Certain features shown may be optional.

Manufactured By:
Helm Welding (1983) Limited
Lucknow, Ontario, Canada

P: 519-529-7000
F: 519-529-3260
www.lucknowproducts.com