

Bush Hog®**Built To Last.****BHT ROTARY TILLERS****FEATURES**

- Contoured hood for excellent material flow
- Adjustable side skids for depth control
- Six tines per flange results in finer chopped material and soil
- Durable, proven side gear
- Spring-loaded rear gate helps smooth out material
- A slip clutch is standard for really tough applications

SPECIFICATIONS

Models	BHT55	BHT67	BHT78
Tractor PTO HP Min. – Max.	20 - 50	30 - 60	40 - 60
Hitch	ASAE Cat 1/QH		ASAE Cat 1&2/QH
Offset	None		
Width of Tillage	55"	67"	78"
(Rotor) # of Flange	7	9	10
No. of Blades	42	54	60
Rotor Speed	212 RPM @540 PTO		
Blades	L Type		
Power to Rotor	Gear		
Transmission Depth of Cut*	7"		
Slip Clutch	Standard		

*May require additional passes depending on soil typeSPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Dealer Info:

**BUSH HOG®**
Performance You Can Count On™www.bushhog.com**Bush Hog®, Inc.**
2501 Griffin Ave., Selma, AL 36703
(334) 874-2700

©Nov 2012 Bush Hog®, Inc.