

# **BUSH HOG®**

## **Estate Commercial Series Zero Turn Mowers**

### **BUSH HOG® FEATURES**

**Commercial Grade Spindles Greased From the Top**

**Rolled Front Edge Deck With Bar For Extra Protection**

**Hydro-Gear ZT 3400 Hydrostats**

**Durable Anti-Scalp Rollers**

**10Gauge Welded Steel**

**Decks Fully Floating Deck**

**Long Lasting Electric Clutches**



<b>Engines and Decks</b>	<b>Width x Length (deflector up)</b>	<b>Dry Weight*</b> (*lbs. with standard seat)
<b>EC2555KH2</b> 25 HP Kohler® Courage Pro engine / 55 inch deck	59 x 82.5	955
<b>EC2561KH2</b> 25 HP Kohler® Courage Pro engine / 61 inch deck	65 x 82.5	980
<b>EC2761KH2</b> 27 HP Kohler® Courage Pro engine / 61 inch deck	65 x 82.5	980
<b>Drive System</b>	Dual hydrostats, Hydro-Gear® ZT 3400™'s with large 7 inch cooling fans	
<b>Brakes</b>	Hydro provides dynamic braking; disc-type parking brake	
<b>Electrical System</b>	12 volt, Rated at 230 CCA; electric start	
<b>Steering/Motor Control</b>	Dampened twin levers with grips, adjustable fore and aft and vertically	
<b>Front Caster Tires</b>	13 x 5.0-6 4 ply tubeless	
<b>Drive Tires</b>	22 x 10.5-12 4 ply	
<b>Speed</b>	Infinitely variable; 0-10 MPH forward	
<b>PTO Engagement</b>	Electromagnetic clutch rated at 175 ft lbs	
<b>Seat Options</b>	High-back, foam padded seat with flip-up arm rests and seat slides High-back full suspension seat with flip-up arm rests and seat slides	
<b>Features/Gauges</b>	Tachometer/hour meter, low engine oil pressure warning light, low engine oil pressure audible alert, high engine temperature warning light and audible alert for Kohler® models, molded-in beverage holder, molded-in storage, large tethered fuel caps	
<b>Safety</b>	Operator Presence Controls (OPC), Certified fold-down ROPS with seatbelt	
<b>Controls</b>	Key ignition, throttle, choke, PTO switch, park brake lever	
<b>Style</b>	10 gauge steel on fully floating, 5 inch deep side discharge	
<b>Deck lift</b>	Quick Foot™ height adjustment from the seat	
<b>Blades</b>	1/4 inch thick, heat-treated high alloy steel, Hi Lift Fusion®	
<b>Cutting Height Range</b>	1 1/2 to 4 1/2 inches, adjustable in 1/4 inch increments	
<b>Blade Tip Speed</b>	18,000 FPM	
<b>Accessories</b>	Grass Mulching Kits, Working Lights, Trailer Hitch Kit, and Bar tires.	

3 year limited warranty (third year parts only) includes drive train, electromagnetic clutch, deck and cutter spindles. See dealer for complete details. Engine warranty administered through engine manufacturer.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE