

Bush Hog® TOUGH

RTH Series Rotary Tillers

BUSH HOG® TOUGH FEATURES

TOUGH Heavy Duty Gearboxes

TOUGH Direct Gear Drive

TOUGH Replaceable Skids

TOUGH Anti-Wrap Device To Protect Seals

TOUGH Slip Clutch Is Standard

TOUGH High Carbon, Long Life Steel Blades

TOUGH Solid Steel Rotors

TOUGH Powder Coat Paint



Model RTH72

MODELS	RTH60-03	RTH72-03	RTH80-03	RTH88
Tilling Width	60 inches	72 inches	80 inches	88 inches
Number of Blades	28	36	40	44
Tractor HP Range	40 - 55 PTO	45 - 55 PTO	55 - 80 PTO	65 - 80 PTO
Type Hitch	Cat. I & II, 3 Point	Cat. I & II, 3 Point	Cat. I & II, 3 Point	Cat. I & II, 3 Point
Offset	12 inch Fixed	None	None	None
Number of Flanges	7	9	10	11
Rotor Speed	213 RPM/540 PTO	213 RPM/540 PTO	213 RPM/540 PTO	213 RPM/540 PTO
Type of Blades	C Type	C Type	C Type	C Type
Power to Rotor Transmission	Gear Drive Single Speed			
Depth of Cut	Adjustable - 7 inches, Position Lock Skid Shoe			
Driveline	Slip Clutch Standard	Slip Clutch Standard	Slip Clutch Standard	Slip Clutch Standard
Approximate Weight	810 lbs	884 lbs	924 lbs	964 lbs
Warranty	1 year limited warranty			