

4 SERIES

64 to 107 Engine HP

Landini®



Tractor Model	4-060	4-070	4-080	4-090	4-100	4-105		
Engine								
Rated Engine Horsepower @ 2200 RPM	HP (kW)	61 (45)	68 (50)	75 (55)	85 (63)	95 (70)		
Rated PTO Horsepower* @ 2200 RPM	HP (kW)	51 (38)	57 (42)	63 (46)	71 (52)	79 (58)		
Max. Engine Horsepower	HP (kW)	64 (47)	72 (53)	79 (58)	90 (66)	99 (73)		
Max. PTO Horsepower*	HP (kW)	54 (40)	61 (45)	68 (50)	76 (56)	85 (63)		
Engine Type		Deutz 2.9L 4-cylinder, liquid cooled diesel			Deutz 3.6L 4-cylinder, liquid cooled diesel			
Emissions System		Tier 4i; Cooled EGR and diesel oxidation catalyst (DOC)						
Fuel Capacity	gal (liter)	23.7 (90)			31.7 (120)			
Drive Train								
Standard Transmission		12x12 shuttle transmission; 4 gears and 3 ranges; 25 mph (40 kph) transport speed						
Optional Transmission		Creeper			Creeper; 2-speed power shift			
Shuttle Type		Synchronized mechanical shuttle standard; hydraulic power shuttle optional						
Rear Axle		Heavy duty cast steel axle with flange; inboard planetary final drives; hydraulic wet disc brakes						
Differential Lock		Fully locking rear; limited slip front			Fully locking front and rear; electro-hydraulic engagement			
4wd Front Axle		Cast steel housing; outboard planetary final drives; hydrostatic power steering						
Hydraulics, 3-point Hitch, PTO								
Implement Hydraulic System Type		Open center hydraulic system; separate implement and steering pumps						
Hydraulic Flow Rate	gpm (lpm)	7.4 (28) for steering; 12.9 (49) to implements			8.5 (32) for steering; 15 (57) to implements			
Remote Valves		2 rear remote valves standard; up to 3 rear valves possible						
Rear 3-point Hitch Type		ASAE Category 2 hitch, telescopic ballends, telescopic stabilizers						
Rear 3-point Lift Capacity	lb (kg)	5,952 (2700) standard, 7,495 (3400) optional			5,952 (2700) standard, 8,600 (3900) optional			
Rear PTO		540 and 1000 RPM speeds standard; push-button engagement; rear fender control						
Operator's Area								
Open Station		2-post folding ROPS; flat foot deck; adjustable steering wheel; suspended vinyl seat; front mud guards						
Cab		4-post structure; 2 doors; flat foot deck; heavy duty HVAC; adjustable steering wheel; available air suspended cloth seat						
Wheelbase	in (mm)	82.7 (2100)			87.8 (2230)			
Height Over ROPS 420/85R30 rear tires	in (mm)				111.0 (2794)			
Height Over Cab 420/85R30 rear tires	in (mm)				97.2 (2470)			
Overall Length with front weights	in (mm)	165.0 (4190)			170.1 (4320)			
Base Weight without Ballast	lb (kg)	6,380 (2900) ROPS / 7,130 (3240) cab			7,025 (3200) ROPS / 7,775 (3540) cab			

* Manufacturers calculated estimates.



2590 Breckenridge Blvd. / Duluth, GA 30096
(866) 327 - 6733 / www.McCormickNA.com

Landini, Landini Logo, McCormick and McCormick Logo are registered trademarks of McCormick International USA in the U.S. and/or other countries. International Harvester and Farmall are trademarks of CNH America LLC. © 2013 McCormick International USA, Inc. All Rights Reserved. The standard and optional equipment and the availability of individual models might vary from one country to the next. McCormick International USA, Inc. reserves the right to undertake modifications without prior notice to the design and technical equipment at all times without this resulting in any obligation whatsoever to make such modifications to units already sold. While every effort is made to ensure that the specifications, descriptions, and illustrations in this brochure are correct at the time of printing, these are also subject to change without prior notice. Illustrations might show optional equipment, and might not show all standard equipment.