

# 3700

**HARD CAB**  
Manufactured  
by Jodale-Perry



**SNOW BLOWER**  
Distributed through  
Kaye Corporation  
[www.kayecorp.com/new](http://www.kayecorp.com/new)

## **OUT-FRONT DECK**

Fully-fabricated deck shell with 11 ga. deck plate doubler with an additional 7 ga. tripler for each spindle mount area. PTO driven deck system containing a hydraulic deck lift; allowing operator to raise or lower deck from comfort of seat, as well as a variable hydraulic weight transfer control, where operator may adjust traction for varying terrain conditions. Deck tilts up to 90 degrees for ease of service.



## **SOFT CAB**

Manufactured  
through Femco  
[www.femcomfg.com](http://www.femcomfg.com)



**ROTARY BROOM**  
Distributed through  
MB Products  
[www.m-bco.com](http://www.m-bco.com)

## **CATCHING SYSTEM**

Heavy Duty Steel frame with sturdy, lightweight aluminum Catcher Box with a capacity of 24 cubic feet (19.3 bushels). Conveniently dump-from-seat using the left hand dumping arm. Blower and adapter kit available on the 60" and 72" deck. Blower is assembled directly to the right-hand side of the mower and powered via belt drive off right side deck spindle.



## **84" FLEX DECK**

Increase productivity with overall deck cutting width of 84". Fully-fabricated deck made of 10 ga. steel with an additional 10 ga. plate reinforcing spindles. Right and left deck wings flex +/- 20 degrees for premium cut quality on varying terrain. Cutting height adjustments from .75" to 3.5".



## **SNOW BLADE**

Strong 60" blade with a 11 ga. reversible 3/8" x 4" tall mold-board that is 18" high. At maximum angle of 30°, you get a blade width of 52" at 15° increments (manual blade adjustment). Engineered with an attack angle of 65° and comes with 100 lb recommended rear counterbalance weights.



**HUSTLER**  
Cutting Grass Not Corners





# 3700

## Hustler 3700 Diesel Specifications

Engine	Hustler 3700
Model	Shibaura N843L

**Type** Liquid-cooled, inline, 3-cylinder, normally aspirated industrial diesel engine

**Starter** 12-volt (1.2 kw), solenoid shift positive engagement

**Charging System** 12-volt, 40-amp alternator

**Oil Filter** Spin-on engine oil filter 6.3 Qt (6.0 l) oil capacity

**Engine Oil** 15W40

**Fuel** #2 diesel

**Fuel Capacity** 13 US Gal (49.2 L)

**Fuel Filter** Heavy-duty, spin-on fuel filter, with sediment bowl

**Injection System** Bosch in-line, indirect injection

**Air Filter** Heavy-duty air filter with safety filter for maximum protection, dry, dual-element

**Cooling** Liquid cooled. Direct-driven, mechanical cooling fan

**Cooling Capacity** 5.6 qt (5.4 L)

**Governor** Mechanical governor with 2700 RPM high idle speed

**PTO** Independent type PTO. PTO speed 2209 RPM

**PTO Clutch** Wet multi-disc manual

### TRACTION DRIVE SYSTEM

**Type** Auto 4WD or Full time 4WD  
Hydrostatic transmission driving, two-speed gear axle

**Filter** 35 micron suction

**Ground Speed** Forward Low: 0-6 mph, High: 0-15 mph  
Reverse Low: 0-4 mph, High: 0-9 mph

**Steering** Hydrostatic power. Tilt & telescoping steering wheel

**Speed Control** 2 pedals forward & reverse.  
2 range hydrostatic transmission, Cruise control

**Brakes** Wet disc (Single pedal control)

**Tires** Front Drive 24 x 12 – 12, turf tread  
Rear Drive 20 x 8 – 10

**Hydraulic Capacity** 8.5 gal (32 L)

**Weight (Power Unit)** 1653lbs (750 Kg)

### GENERAL INFORMATION

**Safety Features** Operator presence system connected to seat, traction pedals and park brake switch. Hand-operated parking brake. Two-post foldable ROPS.

**Headlight** Standard

**Seat Suspension** Molded-vinyl, adjustable seat with armrests. Fore and aft adjustment, suspension adjustment

**Deck Lift** Hydraulic w/adjustable weight transfer

**Controls** Hand-operated throttle, ignition switch, L-N-H & AWD Lock, parking brake, hydraulic lift

**Cup Holder** Single cup holder

**Indicators** Hour meter, temp gauge, oil pressure light, charge light, glow plug light, audible alarm for high engine temperature and low oil pressure, air filter monitor, fuel gauge

### DECKS

	84" REAR DISCHARGE	60" AND 72" SIDE DISCHARGE	72" REAR DISCHARGE
<b>Blades:</b>	(3 LH & 3 RH) 15.00" x .204" low sail	60": (3) 20.5" x .203" high sail 72": (3) 24.5" x .203" high sail	(2 LH & 1 RH) 23.9" x .203" low sail
<b>Spindles:</b>	Ductile housing, 1" diameter shaft, greaseable sealed ball bearings	Ductile housing, 1" diameter shaft, greaseable sealed ball bearings	Ductile housing, 1" diameter shaft, greaseable sealed ball bearings
<b>Blade Tip Speed:</b>	16,900 FPM	60": 17,950 FPM 72": 16,705 FPM	72": 16,550 FPM
<b>Front Gauge Tires:</b>	(4) – 9 x 3.5 – 4 smooth tread, semi-pneumatic	(2) – 13 x 5.0 rib tread, pneumatic	(2) – 13 x 5.0 rib tread, pneumatic
<b>Cutting Height:</b>	0.75" to 3.50" in .25" increments	1" to 6" in .25" increments	1" to 6" in .25" increments
<b>Cutting Widths:</b>	83"	60" & 72"	72"
<b>Trim Capacity:</b>	15" (both sides of mower)	60": 9.5" 72": 15.5"	9.5" (both sides of mower)
<b>Total Weight:</b>	2,428 lbs. includes 84" deck and rear weights (4x50)	60": 2,303 lbs. 72": 2,403 lbs.	72": 2,428 lbs.

### ACCESSORIES

**Mulch Kit** Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil.

**Snow Blower, Snow Blade, Rotary Broom, Debris Blower, Hard Cab, Soft Cab, Remote Hydraulic Kit, Light Kit (ROPS mounted), Beacon Kit (ROPS mounted), Flasher Kit (ROPS mounted)**

**TRACTOR**  
**2** YEAR | **1500** HOUR  
LIMITED WARRANTY

**ENGINE**  
**3** YEAR | **2000** HOUR  
LIMITED WARRANTY

\* See your local Hustler dealer for complete warranty details

Specifications subject to change without notice.

**HUSTLER**   
Cutting Grass Not Corners