

# FASTRAK<sup>®</sup> SDX

**STRONGER, FASTER, TOUGHER WITH COMMERCIAL-GRADE TRANSMISSION, UPGRADED CUSTOM SEAT AND MORE**

## HIGHLIGHTS

- 48", 54" or 60" commercial welded-steel deck
- Heavy-duty fabricated frame – unmatched durability
- Exclusive SmoothTrak<sup>™</sup> steering – responsive, precise control
- Patented automatic parking brake
- Heavy-duty cyclonic air cleaner
- Internal suspension seat with rubber isolated seat mounts

LIMITED  
**LIFETIME WARRANTY**  
FRAME & LEADING EDGE OF DECK



| <b>ENGINE</b>       |   | <b>CONSTRUCTION</b>   |   |
|---------------------|---|---|---|
| Manufacturer        | Kohler Confidant ZT730, ZT740   | Frame   | 1.5" x 3" x .125 " steel  |
| HP                  | 48", 54" deck: 23HP* ZT730<br>60" deck: 25HP* ZT740<br>* Per SAE J 1995                         | Front Axle  | Fabricated with sealed ball bearings                                    |
| Displacement        | 747cc   | Front Caster Wheels   | Heavy duty ball bearing, greasable                                      |
| Cooling             | Air cooled  | Front Caster Forks  | Fabricated 3/8" steel   |
| Engine Warranty     | 3 year  | <b>GENERAL</b>  |   |
| <b>DRIVE SYSTEM</b> |   | Seat  | Custom bolstered vinyl with internal suspension, isolator, and armrests |
| Type                | Dual hydrostatic  | Fuel Capacity   | 5 gallons   |
| Transmission        | Hydro-Gear ZT-3400  | Cup Holder  | Yes   |
| Speed               | 9 mph   | Front Tire  | 48": 13 x 5.0 - 5<br>54", 60": 13 x 6.5 - 6                             |
| Parking Brakes      | Patented automatic  | Drive Tire  | 48": 22 x 9.5 - 10<br>54", 60": 23 x 11 - 10                            |
| <b>DECKS</b>        |   | <b>DIMENSIONS</b>   |   |
| Cutting Width       | Side discharge: 48", 54", 60"   | Weight  | 48": 860 lbs      54": 864 lbs<br>60": 881 lbs                          |
| Cutting Heights     | 1.5"- 4.5"  | Height  | 44.3"   |
| Deck Lift           | Foot operated   | Length  | 48": 73.6"      54": 74.42"<br>60": 75.92"                              |
| Depth               | 5"  | Width w/ chute up   | 48": 49.1"      54": 55.1"<br>60": 61.1"                                |
| Blades              | 3   | Tire Width  | 48": 47"      54", 60": 52"   |
| Blade Length        | 48" deck: 16.5" x 2.5" x .20"<br>54" deck: 18.5" x 2.5" x .20"<br>60" deck: 20.5" x 2.5" x .20" | <b>PRODUCTIVITY*</b>  |   |
| Spindles            | Aluminum with 1.0" shafts and sealed ball bearings  | Acres Per Hour  | 48": 3.49      54": 3.93<br>60": 4.36                                   |
| Drive               | Electric PTO clutch   | <b>OPTIONAL ACCESSORIES</b>   |   |
| Construction        | 10 ga. fabricated   | Mulch kit<br>2-bag power grass catcher<br>LED lights<br>FlexForks<br>Steering extension kit<br>Stripe kit<br>High vacuum deck kit |   |
| Spindle Mounts      | Reinforced 11 ga.   |   |   |
| Impact/Trim Areas   | 3/8" x 1" steel bar   |   |   |

\* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.