

60"



King of the Hill

### FEATURES

- Rated up to 25 degree slope
- A smooth top speed of 10 mph
- Extra length for enhanced performance on hills
- Bar-tread tires for increased traction  
(The tires are mounted backwards for even more holding power while backing up hills.)
- Wheel weights and added frame weight for increased balance and traction
- 13 x 6.50 semi-pneumatic front caster tires - no flats, ever!
- Foot-operated deck-lift system
- Certified 2-post fixed ROPS

**2 YEAR** | **NO**  
HOUR LIMIT  
LIMITED WARRANTY

OR

**5 YEAR** | **500**  
HOUR  
LIMITED WARRANTY

\* See your local Hustler dealer for complete warranty details

**LIMITED**  
**LIFETIME**  
**WARRANTY**  
FRAME & LEADING EDGE OF DECK

\* Original Purchaser Only

[www.hustlerturf.com](http://www.hustlerturf.com)



**HUSTLER**  
Cutting Grass Not Corners

60"

## Engine

Kawasaki FX1000

35HP

More Engine Information:

• [www.kawpower.com](http://www.kawpower.com)

### ENGINE

**Starter:** 12-volt

**Ignition:** Electronic

**Charging System:** 12-volt (see engine manufacturer specs)

**Fuel** Unleaded gasoline (see engine manufacturer specs)

**Fuel Filter:** Replaceable, automotive-type

**Air Filter:** Heavy-duty air cleaner to extend the service

interval for excessive, dirty applications and improved performance

**Cooling:** Air cooled. Fly-wheel fan

**Governor:** Mechanical

### TRACTION DRIVE SYSTEM

**Type:** Dual hydrostatic. Individual pumps power two direct-drive wheel motors. Hydrostatic system operates on 15W50 Mobil 1 synthetic motor oil. Transmission drive (oil) cooler for increased system life.

**Pumps:** Two variable displacement, slipper piston pumps. Each pump powers one drive-wheel. Danfoss DDC-20

**Pump Drive:** B Section V-belt drive from engine crankshaft. Large pulley and idler diameters for longer belt life.

**Hydraulic Lines:** Stainless-steel, high-pressure lines with Parker SealLok™ O-Ring Face-Seal fittings.

**Cooling** Large capacity cooler with 9 inch fan for extended hydraulic life

**Final Drive:** Direct-drive high-torque wheel motors. One for each drive wheel. Parker TG0360 with hot oil shuttle

**Filter:** Internal

**Ground Speed:** Infinitely variable: 0-10 mph

forward, 0-6 mph reverse

**Steering:** SmoothTrak™ twin-lever steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and turns are all controlled with hand-operated controls

**Turning Radius:** True zero turning radius. Turns within its own length. Counter-rotating, independent drive wheels

**Brakes**

**Service:** Hydrostatic dynamic braking

**Parking:** Automotive-style drum brakes. When steering levers are placed in park position, integral park brakes are automatically engaged

**Tires:** Front: 13 x 6.50 – 6, smooth tread, semi pneumatic  
Drive: 26 x 12 – 12, bar tread

**Capacities:** Fuel System: 12 US gal (45.4 l)

Hydraulic Oil: 3 US gal (11.36 l)

### GENERAL INFORMATION

**Safety Features:** Standard fixed ROPS with seat belt. Operator presence system connected to seat, deck clutch and park brake switches. Stabilizer wheels at rear of lawn mower. Side discharge deck with discharge chute.

**Seat:** Molded vinyl suspension seat with armrests. Fore and aft adjustment.

**Construction:** Main frame is 1.5 in x 3 in x .187 in (3.8 cm x 7.62 cm x .47 cm) rectangular steel tubing. Drive motors mounted to 7 ga (.45 cm) welded steel. Front caster wheels mounted with ball bearings on each wheel. Front caster forks are .5 in (1.27 cm) steel.

**Controls:** Hand-operated choke, throttle, ignition switch, electric mower clutch. Integrated parking brakes

**PTO Clutch:** 250 ft. lbs.

**Indicators:** Hour meter, engine warning light

**Cup Holder:** Cup holder molded into the left side fuel tank. Accommodates nearly any cup size.

### DIMENSIONS

**Height:** 71.5 in (181.6 cm) FIXED ROPS

**W/60 in Deck**

Length: 94.3 in (239.5cm)

Overall width: 66 in (167.6 cm) w/discharge chute up

Tire-to-tire width: 57 in (144.78 cm)

Weight: 1788 lbs (811.1 kg)

### DECK

**Side-Discharge:** 60"

**Type:** Free-floating mower using three blades with center blade to the front. Mower deck is suspended at the corners. Includes 3 standard deck-mounted rollers to improve flotation in rolling and uneven terrain.

**Deck Lift:** Raise and lower deck from driver's seat with simple foot-operated deck height adjustment. Pin for setting height, transport position. Change cutting heights, climb curbs and trailer more easily.

**Construction:** Welded steel. Solid 1.5 in x .375 (2.55 cm x .95 cm) steel bars reinforce impact areas on trim edges. Commercial style, box section reinforced front edge.

Reinforcements welded onto spindle mount areas. High density, rubberized discharge chute.

**Cutting Heights:** Foot-operated deck height adjustment. Pin for setting height, detent for transport position.

Height adjustment in .25 in increments from 1 in to 5.5 in (2.55 cm to 13.97 cm).

**Mowing Blades:** Heavy-duty, heat-treated, high-lift steel Fusion™ blades. Fusion blades feature an exclusive electro-fusion technology that creates an ultra-hard layer at the blade's cutting edge, the blade remains sharp and continues to give a clean cut far longer than any blade on the market.

60 in: 20.50 in x 3.00 in x .250 in blade, extra high sail

### Blade Tip Speed:

**Side-Discharge**

60 in: 18,630 fpm

**Deck Drive:** Belt drive from engine with electric clutch to all three spindles. Spring tension idler and large pulleys to extend belt life.

**Spindles:** Ductile iron casting with steel shafts and sealed ball bearings

### Width of Cut

**Side-Discharge**

60 in: 59.25 in (150.5 cm)

### Trim Capacity (left side)

**Side-Discharge**

60 in: 2.5 in (6.35 cm)

### ACCESSORIES

**Mulch Kit:** Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil.

**Gator™ Blades:** Patented mulching blade design

**Wavy Blades:** Improved performance for mulching

**Other Accessories:** Light Kit, Hydraulic Deck Lift, Pneumatic Tire, Steering Lever Extension Kit, Rear Anti-Scalp wheel, Sand Kit, Stripe Kit, Weight Kit.

*Specifications subject to change without notice.*