



HUSTLER[®]
ENGINEERING PERFORMANCE

HUSTLER Z

D I E S E L

- ▶ 54", 60" & 72" side discharge VX4® decks
- ▶ 60" & 72" rear discharge decks
- ▶ Clean, compact, service friendly design
- ▶ Engine mounted sideways for serviceability and compactness
- ▶ Patented belt drive system provides up to 3X longer belt life
- ▶ Over 18,000 fpm blade tip speed - superior quality of cut
- ▶ Wide stance, low center of gravity
- ▶ 12 mph top speed

LIMITED
WARRANTY

2 YEAR | NO LIMIT | 5 YEAR | 500 HOUR

See your local Hustler dealer for complete warranty details

LIMITED
LIFETIME WARRANTY

FRAME & LEADING EDGE OF THE DECK



HUSTLER Z

D I E S E L

ENGINE			
MANUFACTURER	Shibaura	SPINDLE MOUNTS	Reinforced 11ga. doubler +7ga. tripler, steel
HP	25HP - Shibaura Tier 4	IMPACT/TRIM AREAS	1.5" x .375" steel bar protector
DISPLACEMENT	1,131cc		
COOLING	Liquid Cooled, direct-drive, mechanical cooling fan	CONSTRUCTION	
AIR CLEANER	Heavy Duty Canister	FRAME	1.5" x 3.0" x .187" steel
ENGINE WARRANTY	3 year	FRONT CASTER WHEELS	Mounted w/ sealed ball bearings
		FRONT CASTER FORKS	Fabricated 1/2" steel
DRIVE SYSTEM		GENERAL	
TYPE	Dual Hydrostatic	SEAT	Grammer premium susp. seat
PUMPS	Tandem 21cc HydroGear pumps	FUEL CAPACITY	14.4 gal.
WHEEL MOTORS	Parker TG0335	CUP HOLDER	Yes
HYDRAULIC LINES	Stainless Steel Parker Seal Loc Technology	FRONT TIRE	13 x 6.5 - 6
HYDRAULIC COOLING	Oil cooler w/ 8" fan	DRIVE TIRE	54" deck: 24 x 9.5 - 12 60", 72" deck: 24 x 12 - 12
RESERVOIR CAPACITY	2 gal.	DIMENSIONS	
SPEED	12 mph	WEIGHT	54" : 1645 lbs 60" : 1695 lbs 72" : 1760 lbs
PARKING BRAKES	Patented automatic	HEIGHT W/ ROPS UP	69"
DECKS		HEIGHT W/ ROPS FOLDED	51"
CUTTING WIDTH	54", 60", 72"	LENGTH	54" deck: 85.5" 60" deck: 86.8" 72" deck: 90.4"
CUTTING HEIGHTS	1"- 5.5"	WIDTH	54" deck: 59.25" w/ chute up 60" deck: 66" w/ chute up 72" deck: 78" w/ chute up
DECK LIFT	Foot Operated	TIRE WIDTH	54" deck: 52" 60", 72" deck: 56"
DEPTH	5.5"	PRODUCTIVITY*	
BLADES	3	ACRES PER HOUR	54" : 5.01 60" : 5.57 72" : 6.68
BLADE LENGTH	54" deck: 3 - 18.5" x 3.0" x .203" 60" deck: 3 - 20.5" x 3.0" x .203" 72" deck: 3 - 24.5" x 3.0" x .250"		
SPINDLES	Ductile cast iron w/ steel shafts and sealed ball bearings		
DECK BELTS	1		
DRIVE	Electric PTO Clutch		
CONSTRUCTION	11ga. +11ga.+7ga. welded steel		

* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.

Optional Accessories: Mulch Kit, Light Kit, Semi Pneumatic front tires, FlexForks, Steering Extension Kit, Sand Kit, Deck Rear Anti-scalp wheels, Deck Stripe Kit, Hydraulic Deck Lift, Beacon Kit, Flasher Kit, Hitch Kit