

# 36"/42"

## **FastTrak** SUPER DUTY

Hustler flexes its mower muscle.

### FEATURES

- Kawasaki FX Premium Commercial Engines w/ 3yr warranty
- 36" or 42" side-discharge decks
- Commercial welded steel decks
- 20" drive tires, 13" caster tires
- ZT 3100 Commercial Transmission
- Commercial duty deck spindles
- Heavy-duty, 7-gauge, full-height rear bumper with built-in hitch provides protection for the engine and exhaust
- Toughest frame, front forks and deck in the industry
- 4.2-gallon fuel capacity
- Simplest maintenance in the industry
- Seat springs and slide with arm rests come standard
- SmoothTrak™ steering with patented automatic park brake system
- Standard, foldable Certified ROPS and seat belt



\* Original Purchaser Only

LIMITED  
WARRANTY  
**4** YEAR | **800** HOUR  
RESIDENTIAL

OR

LIMITED  
WARRANTY  
**2** YEAR | **800** HOUR  
COMMERCIAL



[www.hustlerturf.com](http://www.hustlerturf.com)

**HUSTLER**   
Cutting Grass Not Corners

# FastTrak

## SUPER DUTY

### 36"/42"

## Engines

**Kawasaki**  
FX600  
19hp

**More Engine Information:**

• [www.kawpower.com](http://www.kawpower.com)

### ENGINE

**Starter:** 12-volt, (see engine manufacturer specs)

**Ignition:** Electronic.

**Charging System:** 12-volt. (see engine manufacturer specs for current rating)

**Fuel:** Unleaded gasoline - maximum of 10% ethanol in fuel. (see engine manufacturer specs)

**Fuel Filter:** Replaceable, automotive-type.

**Air Filter:** Heavy duty canister air cleaner to extend the service interval for excessive, dirty applications and improved performance.

**Cooling:** Air cooled. Fly-wheel fan.

**Governor:** Mechanical.

### TRACTION DRIVE SYSTEM

**Type:** Dual hydrostatic. Commercial-duty Hydro-Gear ZT3100.

**Hydrostatic Drive:** V-belt drive from engine crankshaft.

**Filter:** Spin-on type.

**Ground Speed:** Infinitely variable

**Forward:** 0-7.5 mph (0-12.1 kph)

**Reverse:** 0-4.5 mph (0-7.2 kph)

**Steering:** SmoothTrak™ twin-lever steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and true zero-radius turns are all controlled with hand-operated controls.

**Turning Radius:** True zero radius. Turns within its own length. Counter-rotating, independent drive wheels.

### Brakes:

**Service:** Hydrostatic dynamic braking.

**Parking:** Internal transmission mechanical brake.  
When steering levers are placed in open position, integral park brakes are automatically engaged.

### Tires:

**Front:** 13 x 5.0 – 6, rib tread

**Drive:** 36 in: 20 x 8.0 – 10, turf tread  
42 in: 20 x 10.0 – 10, turf tread

**Capacities:** Fuel System: 4.2 US gal (15.9 l)

### GENERAL INFORMATION

**Safety Features:** Operator presence system connected to deck and drive clutches. Stabilizer rollers at rear of tractor.

**Seat:** Molded-vinyl seat with adjustable armrests. Fore and aft adjustment. Seat-pan suspension springs standard.

**Construction:** Mainframe is 1.5 in x 1.5 in x .188 in (3.8 cm x 3.8 cm x .32 cm) rectangular steel tubing  
Drive motors mounted to .120 in (.45 cm) welded steel  
Front caster wheels mounted with roller bearings on each wheel. Front caster forks are .375 in (.95 cm) steel.

**Controls:** Hand-operated choke/throttle, ignition switch, electric mower clutch. Integrated parking brakes.

**Indicators:** Hour meter.

**Cup Holder:** Cup holder molded into the left side fuel tank. Holds nearly any cup size.

### DIMENSIONS

**Height:** 40 in (101.6 cm)

#### W/36 in Deck:

**Length:** 75.8 in (192.6 cm)

**Overall width:** 36.1 in (91.7 cm) w/discharge chute up

**Tire-to-tire width:** 35.3 in (89.6 cm)

**Weight:** 680 lbs (308 kg)

#### W/42 in Deck:

**Length:** 78.3 in (198.9 cm)

**Overall width:** 42.0 in (106.7 cm) w/discharge chute up

**Tire-to-tire width:** 38 in (96.5 cm)

**Weight:** 690 lbs (312 kg)

### DECKS

**Side-Discharge:** 36" and 42"

**Type:** Free-floating deck using two blades. Deck is suspended at the corners. Includes deck-mounted rollers to improve flotation in rolling and uneven terrain.

**Construction:** 11 ga, .120 in (.30 cm) welded steel with 7 ga, .179 in doubler welded onto spindle mount areas. Solid 1.5 in x .5 in (3.81 cm x 1.27 cm) steel bars reinforce impact areas on trim edges. Steel deck housing is 4 in (10.16 cm) deep which allows high-capacity mowing.

**Cutting Heights:** Foot-operated deck height adjustment. Pin for setting height, detent for transport position. Height adjustment in .25 in increments from 1.5 in to 4.5 in (3.81 cm to 11.4 cm).

**Mowing Blades:** Heavy-duty, heat-treated steel.

**36 in:** 2-17.86 in x 2.5 in x .20 in

**42 in:** 2-20.5 in x 2.5 in x .20 in

### Blade Tip Speed:

**36 in:** 18,400 fpm

**42 in:** 18,100 fpm

**Deck Drive:** Single V-belt drive from engine with electric clutch to the two spindles. Spring tension idler for extended belt life.

**Spindles:** Aluminum casting with steel shafts and sealed ball bearings.

**Discharge Chute:** High density, rubberized.

### Width of Cut:

**36 in:** 35.09 in (89.1 cm)

**42 in:** 40.25 in (102.24 cm)

### Trim Capacity: (left side)

**36 in:** 0.25 in (.635 cm)

**42 in:** 2.25 in (5.75 cm)

### ACCESSORIES

**Mulch Kit:** Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass.

**Flex Forks™:** Shock-absorbing front caster forks for a smooth cut and an even smoother ride.

**2-Bag Catcher:** Powered and non-powered catching systems with 7.2 bushel capacity

**Other Accessories:** Steering Lever Extension Kit, Light Kit

Specifications subject to change without notice.

