

48"/54"/60"

FasTrak SUPER DUTY

Hustler flexes its mower muscle.

FEATURES

- Kawasaki FX Premium Commercial Engines with 3yr warranty
- 48", 54" or 60" side-discharge decks
- Commercial welded steel decks
- ZT 3100 Commercial Transmission
- Heavy-duty, 7-gauge, full-height rear bumper with built-in hitch provides protection for the engine and exhaust
- Toughest frame, front forks and deck in the industry
- Commercial duty, deck spindles
- 6.8-gallon fuel capacity with mechanical fuel gauge
- SmoothTrak™ steering with patented automatic park brake system
- Simplest maintenance in the industry
- 20" drive tires, 13" caster tires
- Seat springs and slide with arm rests come standard
- Standard, foldable Certified ROPS and seat belt



* Original Purchaser Only

LIMITED WARRANTY
4 YEAR | **800** HOUR
RESIDENTIAL

* See your local Hustler dealer for complete warranty details

LIMITED WARRANTY
2 YEAR | **800** HOUR
COMMERCIAL

www.hustlerturf.com



HUSTLER 
Cutting Grass Not Corners

FastTrak

SUPER DUTY

48"/54"/60"

Engines

Kawasaki FX691V 22hp	Kawasaki FX730V 23.5hp
-----------------------------------	-------------------------------------

More Engine Information:

• www.kawpower.com

ENGINE

Starter: 12-volt (see engine manufacturer specs)

Ignition: Electronic

Charging: System 12-volt (see engine manufacturer specs)

Fuel: Unleaded gasoline - maximum of 10% ethanol in fuel (see engine manufacturer specs)

Fuel Filter: Replaceable, automotive-type

Air Cleaner: Heavy-duty, canister style

Cooling: Air cooled. Fly-wheel fan

Governor: Mechanical

TRACTION DRIVE SYSTEM

Type: Dual hydrostatic. Hydro-Gear ZT 3100 commercial-duty pump/motor combination.

Hydrostatic Drive: V-belt drive from engine crankshaft

Filter Spin-on type.

Ground Speed:

Forward: Infinitely variable: 0-8 mph (0-12.9 kph)

Reverse: 0-5 mph (0-8 kph)

Steering: SmoothTrak™ twin-lever steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and turns are all controlled with hand-operated controls

Turning: Radius True zero turning radius. Turns within its own length. Counter-rotating, independent drive wheels

Brakes:

Service: Hydrostatic dynamic braking

Parking: Internal transmission mechanical brake. When steering levers are placed in neutral position, integral park brakes are automatically engaged

Tires:

Front: 13 x 6.5 – 6, smooth tread

Drive: 48 in: 20 x 10 – 10, turf tread
54 in: 20 x 12 – 10, turf tread
60 in: 20 x 12 – 10, turf tread

Capacities:

Fuel System: 6.8 US gal (25.7 l)

GENERAL INFORMATION

Safety Features: Operator presence system connected to deck and drive clutches. Stabilizer rollers at rear of tractor

Seat: Molded-vinyl seat with adjustable armrests. Fore and aft sliding adjustment. Seat-pan suspension springs standard.

Construction: Mainframe is 1.5 in x 1.5 in x .188 in (3.8 cm x 3.8 cm x .48 cm) square steel tubing. Front caster wheels mounted with roller bearings on each wheel. Front caster forks are .375 in (.95 cm) steel

Controls: Hand-operated choke/throttle, ignition switch, electric mower clutch. Integrated parking brakes

Indicators: Mechanical Fuel Gauge

Cup Holder: Single Cup Holder

DIMENSIONS

Height: 41.8 in (106.17 cm)

W/48 in Deck:

Length: 74.42 in (189.02 cm)

Overall width: 50.3 in (127.7 cm) w/discharge chute up

Tire-to-tire width: 47 in (119.38 cm)

Weight: 835 lbs (378 kg)

W/54 in Deck:

Length: 74.42 in (189.02 cm)

Overall width: 56.2 in (142.7 cm) w/discharge chute up

Tire-to-tire width: 51 in (129.54 cm)

Weight: 860 lbs (390 kg)

W/60 in Deck:

Length: 75.92 in (193 cm)

Overall width: 62.7 in (159.26 cm) w/discharge chute up

Tire-to-tire width: 51 in (129.54 cm)

Weight: 885 lbs (401 kg)

DECKS

Side-Discharge: 48", 54" or 60"

Type: Free-floating deck using three blades with center blade to the front. Deck is suspended at the corners. Includes 4 deck-mounted rollers to improve flotation in rolling and uneven terrain

Construction: 11 ga, .120 (.30 cm) welded steel with 11 ga, .120 in (.30 cm) doubler welded onto spindle mount areas. Solid 1 in x .375 (2.55 cm x .95 cm) steel bars reinforce

impact areas on trim edges. Commercial-style box-section reinforced front edge.

Cutting Heights: Foot-operated deck height adjustment. Pin for setting height, detent for transport position. Height adjustment in .25 in increments from 1.5 in to 4.5 in (3.81 cm to 11.43 cm)

Mowing Blades: Heavy-duty, heat-treated, high-lift steel

48 in: 16.5 in x 2.5 in x .20 in

54 in: 18.5 in x 2.5 in x .20 in

60 in: 20.5 in x 2.5 in x .20 in

Blade Tip Speed: (at 3600 RPM engine speed)

48 in: 18,600 fpm

54 in: 18,910 fpm

60 in: 18,410 fpm

Deck Drive: V-belt drive to all three spindles. Spring tension idler for extended belt life.

Spindle: Aluminum casting with steel shafts and sealed ball bearings.

Discharge Chute High density, rubberized

Width of Cut:

48 in: 47.1 in (120 cm)

54 in: 53.1 in (135 cm)

60 in: 59.1 in (150 cm)

Trim Capacity: (left side)

48 in: 0.5 in (1.25 cm)

54 in: 2.5 in (6.5 cm)

60 in: 5.9 in (15 cm)

ACCESSORIES

2-Bag Catcher: Commercial-duty, 7.2 bushel, rear-mounted, two-bag catcher

Mulch Kit: Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil

Flex Forks™: Shock-absorbing front caster forks for a smooth ride and smoother cut

Other Accessories: Light Kit, Stripe Kit, Steering Lever Extension Kit

Specifications subject to change without notice.

