

60" / 72"

H SuperZ HD

Hard to be humble when you're perfect.

FEATURES

- HyperDrive™ Hydro System - Industrial Grade Pumps and Motors
- VX4® Deck Technology provides the best finished appearance period!
- 26" Drive Tires
- SmoothTrak™ Steering - responsive precise control
- Kawasaki FX Premium Commercial Duty Engines w/ 3 yr warranty
- 16 MPH

3 YEAR | **NO**
HOUR LIMIT
LIMITED WARRANTY

* 3RD YEAR PARTS ONLY

OR

5 YEAR | **500**
HOUR
LIMITED WARRANTY

* See your local Hustler dealer for complete warranty details

LIFETIME
WARRANTY
* LIMITED *
FRAME & LEADING EDGE OF DECK

* Original Purchaser Only

www.hustlerturf.com

5 YEAR | **3000**
HOUR
ON TRANSMISSIONS



HUSTLER®
Cutting Grass Not Corners 

SuperZ HD

Engines

Kawasaki

FX850
27HP

Kawasaki

FX1000
35HP

Kohler (CA only)

CV980
38HP

60" / 72"

More Engine Information:

• www.kawpower.com

• www.kohlerengines.com

ENGINE

Ignition: Electronic

Charging System: 12-volt (see engine manufacturer specs)

Fuel Unleaded gasoline

Air Filter: Heavy-duty canister air cleaner to extend the service interval for excessive, dirty applications and improved performance. Dual element.

Cooling: Air cooled.

HD TRACTION DRIVE SYSTEM - Industry Exclusive, Heavy Duty

Type: Dual hydrostatic. Individual pumps power two direct-drive wheel motors. Hydrostatic system operates on 15W50 Mobil 1 synthetic motor oil. Large aluminum transmission drive (oil) cooler for increased system life and reliability.

Pumps: Danfoss DDC-20. Two variable displacement, industrial slipper piston pumps. Each pump powers one drive-wheel.

Pump Drive: Large B Section V-belt drive from engine. Large pulley and idler diameters for longer belt life.

Hydraulic Lines: Stainless-steel, high-pressure lines with Parker SealLok™ O-Ring Face-Seal fittings.

Cooling Large capacity aluminum cooler with 9 inch fan for extended hydraulic life

Final Drive: Direct-drive high-torque wheel motors. One for each drive wheel. Parker TG0280 with hot oil shuttle

Hot Oil Shuttle: Continuously moves hot oil from wheel motor to cooler while supplying fresh cool oil

Filter: Internal micron

Ground Speed: Infinitely variable: 0-15.5 mph (0-24.9 kph) forward, 0-7.5 mph (0-12.07 kph) reverse

Steering: SmoothTrak™ twin-lever steering provides independent control of each drive wheel.

Turning Radius: True zero turning radius. Turns within its own length. Counter-rotating, independent drive wheels

Brakes

Service: Hydrostatic dynamic braking

Parking: Patented automatic parking brake when steering levers are placed in neutral position. Automotive-style drum brakes.

Tires: Front: 13 x 6.50 – 6, rib tread, pneumatic
Drive: 26 x 12 – 12, turf tread

Capacities: Fuel System: 12 US gal (45.4 l)
Hydraulic Oil: 3 US gal (11.36 l)

GENERAL INFORMATION

Safety Features: Standard foldable ROPS with seat belt. Operator presence system connected to seat, deck pto and park brake switches. Stabilizer wheels at rear of lawn mower. Side discharge deck with discharge chute and rear discharge

deck with deflectors.

Seat: Michigan suspension seat with armrests. Fore and aft adjustment OR Grammar suspension seat with isolators.

Construction: Main frame is 1.5 in x 3 in x .187 in (3.8 cm x 7.62 cm x .47 cm) rectangular steel tubing with internal gussets in frame bend. Drive motors mounted to 7 ga (.45 cm) welded steel. Front caster wheels mounted with ball bearings on each wheel. Front caster forks are .5 in (1.27 cm) steel rotating on 2 inch sealed ball bearings

Controls: Hand-operated choke, throttle, ignition switch, electric mower clutch. Integrated parking brakes

PTO Clutch: 250 ft. lbs. Heavy Duty

Indicators: Hour meter, engine warning light

Cup Holder: Cup holder molded into the left side fuel tank. Accommodates nearly any cup size.

DIMENSIONS

Height: 54 in (137 cm) ROPS folded down
71.5 in (181.6 cm) ROPS up

W/60 in Deck

Length: 84.5 in (214.6 cm)
Width: 66 in (167.6 cm) w/discharge chute up
Tire-to-tire width: 57 in (144.78 cm)
Weight: 1515 lbs (687.2 kg)

W/72 in Deck

Length: 86.7 in (220.2 cm)
Width: 78 in (198.12 cm) w/discharge chute up
Tire-to-tire width: 60 in (152.4 cm)
Weight: 1600 lbs (725.75 kg)

DECKS

Side-Discharge: 60" 72"

Rear-Discharge: 60" 72"

Type: VX4 Decks

Construction: 11ga. with 11ga. doubler and 7ga. tripler
Welded steel. Solid 1.5 in x .375 (2.55 cm x .95 cm) steel bars reinforce impact areas on trim edges. Commercial box section reinforced front edge. Reinforcements welded onto spindle mount areas. High density, rubberized discharge chute

Cutting Heights: Foot-operated deck height adjustment with transport position. Height adjustment in 1/4in increments from 1 in to 5.5 in (2.55 cm to 13.97 cm).

Deck Lift: Raise and lower deck with simple foot-operated deck height adjustment and transport position.

Mowing Blades: 3 Heavy-duty, heat-treated, high-lift steel Fusion™ blades. Fusion blades feature an exclusive electro-fusion technology that creates an ultra-hard layer at the

blade's cutting edge, the blade remains sharp and continues to give a clean cut far longer than any blade on the market.

60 in: 20.50 in x 3.00 in x .250 in blade, extra high sail

72 in: 24.50 in x 3.00 in x .250 in blade, extra high sail

Blade Tip Speed: (at 3600 RPM engine speed)

Side-Discharge **Rear-Discharge**

60 in: 18,630 fpm 60 in: 18,630 fpm

72 in: 18,530 fpm 72 in: 18,040 fpm

Deck Drive: Belt drive from engine with electric clutch to all three spindles. Spring tension idler system and large pulleys to extend belt life. No tools needed for belt adjustment or replacement.

Spindles: Ductile iron casting with steel 1 1/4in shafts and 3in sealed ball bearings

Width of Cut

Side-Discharge **Rear-Discharge**

60 in: 59.25 in (150.5 cm) 60 in: 59.10 in (150.11 cm)

72 in: 71.25 in (180.9 cm) 72 in: 69.20 in (175.77 cm)

Trim Capacity (left side)

Side-Discharge **Rear-Discharge**

60 in: 2.5 in (6.35 cm) 60 in: 1.0 in (2.54 cm)

72 in: 8.0 in (20.32 cm) 72 in: 4.5 in (11.43 cm)

ACCESSORIES

Catcher: Commercial-duty, 12 bushel, rear-mounted, three-bag catcher. Easy on, easy off.

BacVac: Electric accuated DFS catcher system. Easy-on, easy-off versatility. 10 bushel capacity.

Mulch Kit: Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil.

Gator™ Blades: Patented mulching blade design

Wavy Blades: Improved performance for mulching

Flex Forks™: Shock-absorbing front caster wheel forks for a smooth ride and a smoother cut.

Other Accessories: Light Kit, Hydraulic Deck Lift, Steering Lever Extension Kit, Rear Anti-Scalp wheel, Sand Kit, Stripe Kit, Semi-pneumatic tire.

Specifications subject to change without notice.