

36"/48"/54"

TrimStar

With the Trimstar hydro, we definitely walk the walk.

FEATURES

- Kawasaki FS Premium Commercial Duty Engines
 - 3yr warranty
- 36", 48" or 54" side discharge decks
- Patented H-Bar™ steering system
 - Comfortable, User Friendly!
- Wide stance for increased stability
- 3.4-gallon fuel tank
- No daily lube points
- Superior drive system - integrated, serviceable ZT2800 transmissions
- Floating decks adjustable from operator's position

2 YEAR | **NO** HOUR LIMIT
LIMITED WARRANTY

* See your local Hustler dealer for complete warranty details



* Original Purchaser Only

www.hustlerturf.com

HUSTLER 
Cutting Grass Not Corners

TrimStar

36"/48"/54"

Engines

Kawasaki FS481	Kawasaki FS541	Kawasaki FS600	Kawasaki FS691(Electric Start)
14.5hp	15hp	18.5hp	23hp

More Engine Information:

• www.kawpowr.com

Starting: Recoil (electric start on FS691)

Ignition: Electronic

Charging System: 12-volt (see engine manufacturer specs)

Fuel: Unleaded gasoline - maximum of 10% ethanol in fuel (see engine manufacturer specs)

Fuel Filter: Replaceable, automotive-type

Air Cleaner: Dual element

Cooling: Air cooled. Fly-wheel fan

Governor: Mechanical

TRACTION DRIVE SYSTEM

Type: Dual hydrostatic. Hydro-Gear ZT 2800

Pump Drive: V-belt drive from engine crankshaft

Ground Speed:

Forward: Infinitely variable 0-6.3 mph (0-10.1 kph)

Reverse: 0-2 mph (0-3.2 kph)

Steering: Patented, self-centering H-Bar™ Steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and turns are all controlled with the easy to learn, easy to operate H-Bar Steering.

Turning Radius: True zero turning radius. Turns within its own length. Counter-rotating, independent drive wheels

Brakes:

Service: Hydrostatic dynamic braking

Parking: Internal transmission mechanical brake.

Tires:

Front: Two - 11 x 4 - 4, smooth, semi-pneumatic

Drive: 36 in: 18 x 6.50 - 8, turf tread

48 in: 20 x 10 - 10, turf tread

54 in: 20 x 10 - 10, turf tread

Capacities

Fuel System: 3.4 US gal (12.9 l)

GENERAL INFORMATION

Safety Features: Operator presence safety-interlock system. Side discharge deck with discharge chute

Construction: Mainframe is 1.50 x 2.00 x .120 wall steel tubing.

Controls: Hand-operated throttle/choke, ignition switch, mower clutch switch

Indicators: Hour meter, oil pressure warning light (electric start model only)

DIMENSIONS

Height: 40.9 in (103.8 cm)

W/36 in Deck:

Length: 75 in (190.5 cm)

Overall Width: 38 in (96.5 cm) w/dischute up

Tire-to-tire Width: 35 in (88.9 cm)

Weight: 581 lbs (263.5 kg)

W/48 in Deck:

Length: 75 in (190.5 cm)

Overall Width: 50.4 in (128.02 cm) w/dischute up

Tire-to-tire Width: 46.75 in (118.7 cm)

Weight: 660 lbs (2699 kg)

W/54 in Deck:

Length: 76.12 in (193.34 cm)

Overall width: 56.5 in (143.5 cm) w/dischute up

Tire to Tire: 46.75 in (118.74 cm)

Weight: 685 lbs (310 kg)

DECKS

Side Discharge: 36", 48" or 54"

Type: 36" fixed, side-discharge using two blades. No anti-scalp wheels. 36" decks are suspended by solid links in three places. 48" and 54" free-floating, side-discharge using three blades. Deck-mounted anti-scalp wheels to improve flotation in rolling and uneven terrain. 48/54" decks are suspended by chains in four corners.

Construction: 36 in Deck: 7-gauge deck plate with 11-gauge doublers. 48/54 in Deck: 11-gauge deck plate with 11-gauge doublers. 1" x 3/8" steel bar reinforced impact areas on front and trim edges, heavily-reinforced front edge. Lifetime warranty on leading edge of deck. Deck housing is 4 in deep to provide room for high-capacity mowing discharge side

Cutting Heights: Hand operated deck-lift in .25 in increments from 1.5 in to 4.5 in (.1 cm increments, 3.18 cm to 11.43 cm)

Main Blades: Heavy-duty, heat-treated, 10B38 steel blades

36 in Deck: 20.5 in x 2.50 in x .204 in RH blade
13.75 in x 2.50 in x .204 in LH blade

48 in Deck: 16.5 in x 2.50 in x .204 in

54 in Deck: 18.5 in x 2.50 in x .204 in

Mowing Blades: Heavy-duty, heat-treated, high-lift steel Fusion™ blades. Fusion blades feature an exclusive electro-fusion technology that creates an ultra-hard layer at the blade's cutting edge, the blade remains sharp and continues to give a clean cut far longer than any blade on the market.

Blade Tip Speed: 36 in: 18,400 fpm
48 in: 18,600 fpm
54 in: 18,920 fpm

Deck Drive: V-belt drive from engine with electric clutch to spindles. Spring tension idler pulleys

Discharge Chute: High density, rubberized

Trim Capacity (left side):

36 in: 0 in (0 cm)

48 in: 1.2 in (5.08 cm)

54 in: 5 in (12.7 cm)

ACCESSORIES

Mulch Kits: Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil

Deck-Mounted Catcher: Easily-installed, side-mounted catcher holds 3.5 bushels.

Compatible with after-market sulkies and trailers

Specifications subject to change without notice.

